

# Environmental Product Declaration

for Ecosmart Rigid Jeans trousers  
in accordance with ISO 14025



## Programme:

The International EPD® System, [www.environdec.com](http://www.environdec.com)  
EPD Turkey, [www.epdturkey.org](http://www.epdturkey.org)

## Programme Operator:

EPD International AB & EPD Turkey

**Date Of Publication (issue):** 2020-03-20

**Date of Validity:** 2025-02-16

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)

EPD Registration Number: S-P-01793



THE INTERNATIONAL EPD® SYSTEM



ENVIRONMENTAL PRODUCT DECLARATIONS



EPD for 90-100% cotton & 0-10% polyester jeans





# 01 PROGRAMME INFORMATION



## Programme Operator

EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden  
E-mail: [info@environdec.com](mailto:info@environdec.com)

Regional Office: EPD Turkey, Nef 09 B Blok 7/15 Kağıthane/ Istanbul, Turkey  
[www.epdturkey.org](http://www.epdturkey.org)

## Product Category Rules (PCR)

Trousers, shorts and slacks and similar garments  
2019:06, version 1.01  
UN CPC 282

## PCR Review Was Conducted By

The Technical Committee of the International EPD® System. A full list of members available on [www.environdec.com](http://www.environdec.com).  
Chair of the PCR review: Hüdai Kara Contact via: [info@environdec.com](mailto:info@environdec.com)

## Verification

Independent verification of the declaration and data, according to ISO 14025:2006:

☐ EPD process certification ☒ EPD verification

## Third Party Verifier

Nikolay Minkov, Eng. MSc.  
LCA and Sustainability Specialist, Independent EPD Verifier  
Schwartzkopffstrasse 3, 10115, Berlin, Germany  
E-mail: [niks.minkov@gmail.com](mailto:niks.minkov@gmail.com)  
Accredited or approved by: The International EPD® System

## Data Follow Up

Procedure for follow-up of data during EPD validity involves third party verifier:

☐ YES ☒ NO

## LCA Study & EPD Design Conducted By

Semtrio Sustainability Consulting  
AND Plaza No:10-12 Kozyatağı Istanbul/Turkey  
[www.semtrio.com](http://www.semtrio.com)

**UN CPC Class:** 2823

---

Owner of the Declaration: Martelli

Manufacturer: Sanko Tekstil İşletmeleri San. ve Tic. A.Ş. Martelli Şubesi  
Organize Sanayi Bölgesi 3. Cadde No:13, İnegöl/Bursa, Turkey

Martelli has the sole ownership, liability and responsibility of this EPD. For further information about this EPD or its content, please contact Mr. Burak Can at [bcan@martelli.com.tr](mailto:bcan@martelli.com.tr)

EPDs within the same product category but from different programmes may not be comparable.

A woman with blonde hair, wearing a black leather jacket, a grey sweater, blue jeans with rips, and brown boots, is walking on a sandy path. She has a brown backpack. To her left is a rustic wooden fence. In the background, the ocean and a cloudy sky are visible.

02

**MARTELLI**  
WHERE COLLECTIONS  
BECOME REALITY



## DISCOVER MARTELLI

Martelli is an exclusive denim production, washing and finishing facility. Creating limited-edition sample runs for ISKO and exclusive collections for deluxe labels.

With a facility over 25 000 square meters and a team of over 300 research and development specialists, Martelli Turkey is capable to cover 30 000 pieces of denim in their laundry per month.

## HISTORY

As a denim laundry with more than 50 years of experience, Martelli is known for its creativity and innovation in denim finishing and garment dyeing. In 2004 Martelli Turkey was established by a joint-venture between Martelli Group and ISKO. Over the years Martelli Turkey and Martelli Italy have worked closed and shared their knowledge to renovate and challenge itself to add value to the products and denim and the fashion world. Martelli Turkey is now operating as an exclusive denim laboratory for ISKO.





# 03 PRODUCT INFORMATION




# PRODUCT INFORMATION

**Ecosmart Rigid Jeans** is a sustainable version of Smart Jeans processes where water consumption and electricity consumption can be reduced up to 40%. With this product group the chemical bleaching methods have been eliminated. Low-temperature enzymes are used to get stone wash look.

Product Characteristics*	Test Method	Units
For woven materials: Abrasion Strength	EN ISO 12947-2	Over 20000 rubs
For woven materials: Tear Strength	ASTM D1424	Warp: 5114 kg Weft: 5497 kg
For woven materials: Tensile Strength	ASTM D5034	Warp: 49.27 kg Weft: 31.74 kg
Voluntary: For woven materials: Seam Slippage	ASTM D1683	7 kg (min)
pH of water extract	ISO 3071	7.2
Colour fastness to artificial light: Xenon arc fading lamp test	EN ISO 105 B02	6
Acid and Alkaline Perspiration	EN ISO 105 E04	4.5
Dry and Wet Rubbing	AATCC 8	Dry: 4.0 Wet: 2.5

Materials in the Product	% in the product	Material Composition	Compliance with REACH
Fabric	92.4%	90-100% cotton 0-10% polyester	✓
Paper Labels	0.79%	100% Paper	✓
Metal Accessories	6.8%	100% Metal	✓



Chemicals used in Martelli manufacturing comply with the Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

**Packaging:** PE packaging film is used to cover the end products. Classified as Distribution Packaging: designed for the purposes of transport, handling and/or distribution.

*\*The functional unit does not take into account all technical, functional and aesthetic properties of the product. For comparability of products based on the same PCR, these aspects shall also be considered. Weave, Mass per unit area, Width are not disclosed due to being trade secrets.*





# 04 LIFE CYCLE ASSESSMENT



# LIFE CYCLE ASSESSMENT

The International EPD® System has adopted an LCA calculations procedure, which is separated into three different life cycle stages:

- **Upstream module (from cradle-to-gate):** Harvesting of cotton, extraction of man-made fibres, production of yarns and production of fabric, extraction and production of the chemicals.
- **Core module, manufacturing processes (from gate-to-gate):** Transportation of raw materials to the core, manufacturing processes, impacts generated by fuel burned, impacts due to the electricity production and transport with in the production plant.
- **Downstream Processes (from gate-to-grave):** Transportation from preparation to an average retailer. Use phase and end of life phase are excluded from the system boundary due to the aim of the EPD is to be used as B2B communication. The impacts of the downstream processes are negligible as being lower than 1% in the entire system boundary and not declared separately in the EPD.

## Geographical scope of the EPD

Worldwide

## Declared Unit

The declared unit is defined as 1 pair of trousers.

## EPD Type (System Boundry)

Cradle-to-customer

## Data Collection

Specific data (primary data) was used for the Core Module and gathered from the Martelli Manufacturing Plant. The only main material in the end product is fabric and LCA information has been provided by the fabric manufacturer and inserted into Simapro. Data represents the period from 1<sup>st</sup> January 2019 to 31<sup>st</sup> August 2019. For secondary data Ecoinvent v3.5 datasets were used. LCA was modelled in SimaPro v9.0.0.31.

## Allocation

No allocation conducted for input materials and energy consumption was collected specifically per declared unit.

## Cut-Off Rules

Waste and wastewater generated from core presses have been excluded due to the cut-off rule. Impacts caused by treatment operations have been calculated lower than 1% environmental relevance. Transportation to core processes was found negligible <1% for all categories.

## Calculation Methods


All resource use values are calculated from Cumulative Energy Demand V1.11 in SimaPro outputs; net use of fresh water from SimaPro Inventory results. Potential environmental impacts are calculated with the CML-IA baseline V 3.05, Acidification potential from CML non-baseline V 3.04, Formation potential of tropospheric ozone (POCP) from LOTOS-EUROS as applied in ReCiPe Midpoint (H) v 1.13 2008, methods in SimaPro software.



UPSTREAM

CORE

DOWNSTREAM





A first-person perspective of a hiker's feet on a rocky trail. The hiker is wearing dark blue pants and light-colored sneakers. The trail is rocky and surrounded by dense green vegetation. A large white number '05' is overlaid on the left side, and the text 'ENVIRONMENTAL PERFORMANCE' is overlaid in white capital letters to its right.

# 05 ENVIRONMENTAL PERFORMANCE



## Resource Use

Parameter		Unit	Upstream	Core	Total
Primary energy resources – Renewable	Use as energy carrier	MJ, net calorific value	15.81	4.01	19.82
	Used as raw materials	MJ, net calorific value	0.00	0.00	0.00
	TOTAL	MJ, net calorific value	15.81	4.01	19.82
Primary energy resources – Non-renewable	Use as energy carrier	MJ, net calorific value	39.0	44.2	83.2
	Used as raw materials	MJ, net calorific value	0	0	0
	TOTAL	MJ, net calorific value	38.98	44.2	83.2
Secondary material		kg	0	0	0
Renewable secondary fuels		MJ, net calorific value	0	0	0
Non-renewable secondary fuels		MJ, net calorific value	0	0	0
Net use of fresh water		m <sup>3</sup>	0.618	0.040	0.658

## Output Flows

Parameter	Unit	Upstream	Core	Total
Components for reuse	kg	-	0	-
Material for recycling	kg	-	0.042	0.042
Materials for energy recovery	kg	-	0	-
Exported energy, electricity	MJ	-	0	-
Exported energy, thermal	MJ	-	0	-

## Environmental Impacts

Parameter		Unit	Upstream	Core	Total
Global warming Potential (GWP100a)	Fossil	kg CO <sub>2</sub> eq	2.70	3.27	5.97
	Biogenic	kg CO <sub>2</sub> eq	0.246	0.056	0.302
	Land use and land transformation	kg CO <sub>2</sub> eq	0.010	0.014	0.024
	Total	kg CO <sub>2</sub> eq	2.96	3.34	6.3
Abiotic depletion (elements)		kg Sb eq	1.01E-05	6.02E-07	1.07E-05
Abiotic depletion (fossil fuels)		MJ	33.0	39.2	72
Photochemical oxidation		kg NMVOC eq	0.008	0.007	0.016
Acidification		kg SO <sub>2</sub> eq	0.022	0.014	0.036
Eutrophication		kg PO <sub>4</sub> <sup>3-</sup> eq	0.004	0.002	0.006
Water scarcity		m <sup>3</sup> eq	21.0	0.847	21.8

## Waste Production

Parameter	Unit	Upstream	Core	Total
Hazardous waste	kg	-	0.006	0.006
Non-hazardous waste	kg	-	0.008	0.008
Radioactive waste	kg	-	0.00	0.00



- ISO 14040: 2006 Environmental management | Life cycle assessment | Principles and framework
- ISO 14044: 2006 Environmental management | Life cycle assessment | Requirements and guidelines
- ISO 14025: 2006 Environmental labels and declarations | Type III environmental declarations | Principles and procedures
- The International EPD® System | [www.environdec.com](http://www.environdec.com)
- The International EPD® System | The General Programme Instructions v3.01
- The International EPD® System | Trousers, shorts and slacks and similar garments. 2019:06, version 1.01
- **Ecoinvent 3.5** | <http://www.ecoinvent.org>
- **SimaPro LCA Software** | <https://simapro.com>
- **Martelli Denim** | [www.martellidenim.com](http://www.martellidenim.com)
- **LCA Report for Martelli Denim**

## Third Party Verifier

Nikolay Minkov, Eng. MSc.

LCA and Sustainability Specialist, Independent EPD Verifier

Schwartzkopffstrasse 3, 10115, Berlin, Germany

E-mail: [niks.minkov@gmail.com](mailto:niks.minkov@gmail.com)

Accredited or approved by: The International EPD® System



## Owner of the Declaration

Sanko Tekstil İşletmeleri San. ve Tic. A.Ş. Martelli Şubesi

Havaalanı Cd. No:13, 16400 Süleymaniye Osb/İnegöl/Bursa, Turkey

[www.martellidenim.com](http://www.martellidenim.com)



## LCA Author & EPD Design

Semtrio Sustainability Consulting AND Plaza No:10-12 Kozyatagi

Istanbul | Turkey

[www.semtrio.com](http://www.semtrio.com)





Sanko Tekstil İşletmeleri San. ve Tic. A.Ş. Martelli Şubesi

*Organize Sanayi Bölgesi 3. Cadde, No:13, İnegöl/Bursa, Turkey*

[Info@martellidenim.com](mailto:Info@martellidenim.com)

+90 224 714 85 17

+90 224 714 85 11

