




Environmental Product Declaration

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

Firetect Graphite sealant fire-rated



Publication Date

2023-09-19

Valid until

2028-09-18

Owner of Declaration

KLF Productions B.V.

LCA practitioner

Hedgehog Company B.V.

Programme

The International EPD® System,
www.environdec.com

Program Operator

EPD International AB

EPD number

S-P-03622



An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com



General information

Programme information

Programme	The International EPD® System
Address	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
Website	www.environdec.com
E-mail	info@environdec.com

Accountabilities for PCR, LCA and independent, third-party verification
Product Category Rules (PCR)
ISO standard ISO 21930 and CEN standard EN 15804 serve as the core Product Category Rules (PCR)
Product Category Rules (PCR): PCR 2019:14 Construction products, version 1.2.5
PCR review was conducted by: The Technical Committee of the International EPD® System. See www.environdec.com/TC for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat www.environdec.com/contact .
Complimentary Product Category Rules (cPCR): PCR 2019:14-c-PCR-017 c-PCR-017 Technical-chemical products (for construction sector) (c-PCR to PCR 2019:14) (adopted from EPD Norway 2022-07-08)
cPCR review was conducted by: The Norwegian EPD Foundation (EPD-Norge), The Federation of Norwegian Construction Industries (BNL), Saint-Gobain, Byggevarer AS, Hey'di AS, SIKA Norge AS, Mapei AS.
Life Cycle Assessment (LCA)
LCA accountability: Zoë Tan, Hedgehog Company Zoe@hhc.earth Turbinestraat 6, 1014 AV Amsterdam, The Netherlands
Third-party verification
Independent third-party verification of the declaration and data, according to ISO 14025:2006, via: <input checked="" type="checkbox"/> EPD verification by individual verifier Third-party verifier: Matthew Fishwick, Fishwick Environmental Ltd. Approved by: The International EPD® System
Procedure for follow-up of data during EPD validity involves third party verifier:



Yes No

[Procedure for follow-up the validity of the EPD is at minimum required once a year with the aim of confirming whether the information in the EPD remains valid or if the EPD needs to be updated during its validity period. The follow-up can be organised entirely by the EPD owner or together with the original verifier via an agreement between the two parties. In both approaches, the EPD owner is responsible for the procedure being carried out. If a change that requires an update is identified, the EPD shall be re-verified by a verifier]

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

EPDs of construction products may not be comparable if they do not comply with EN 15804+A2.



Product description

This EPD concerns Firetect Graphite sealant fire-rated. The sealant is a high expanding pressure building mastic and can be used for sealing pipe penetrations and cable entries, in a smoke-tight and fire resistant manner, widely tested resulting in an extensive field of application. The basic technical specifications of the product are given in table 1. The product is produced by KLF in Gorinchem, The Netherlands, and sold in cartridges of 310 ml or foils up to 600 ml. Figure 1 shows a cartridge produced by KLF. This EPD studies one kg of sealant, based on a cartridge of 310 ml. The product falls under the UN CPC class 3511.

Table 1. Technical specifications of the Firetect Graphite sealant fire-rated.

Characteristic	Value
Fire resistance (EN 1366-3 + EN 1366-4; EN 13501-1; EN 13501-2)	EI 20 t/m EI 240, depending on application and configuration Class F
Smoke resistance (EN 1634-3)	Sa - S200
Acoustic performance (EN 10140-2 + ISO 717-1)	30 dB t/m 60 dB, depending on application and configuration
pH value	8,0
Durability (EAD 350141-00-1106)	Z ₂ , indoor use

Company

Since 1998, KLF produces and markets a wide variety of specialised high performance passive fire protection products for load bearing structural steel protection, fire rated non-loaded walls, ceilings and penetration seals. Our mission is to keep our high standards in fire performance combined with economics, whilst minimising the impact to the environment. Meeting these environmental requirements in an on-going process to strive for even better sustainability, along with excellent fire protection performance that offers a wide range of applications makes Firetect products leading.

The production facilities employ highly efficient management systems compliant with ISO 9001 and 14001 standards, ensuring optimal operations. Our supply chain is committed to upholding social responsibility principles. Additionally, our load-bearing steel structures, linear joints, and penetration seals adhere to the CE/ETA classification based on EN 13501 standards.

Please consult our website for the Firetect product range, environmental sustainability and the field of application.

Firetect for fire safe buildings.

Manufacturer	KLF Productions BV
Address, corporate office and production site	Techniekweg 11 4207 HC Gorinchem, The Netherlands
E-mail	info@klf.nl
Phone	+31 345 63 97 97



Website	www.klf.nl
Production Location	Gorinchem, The Netherlands

EPD scope and background

Reference Service Life	N.A.
Declared Unit	1 kg of Firetect Graphite sealant fire-rated, as applied

The data of a 310 ml tube was collected and extrapolated to 1 kg product.

The Ecoinvent v3.8 database is used as a source of secondary data. The study meets the requirements of NEN-EN ISO 14025:2010 [1] and the EN 15804+A2:2019 [2]. This EPD follows the PCR 2019:14 v1.2.5 [3], General Programme Instructions v4.0 [4] and c-PCR-017 Technical-chemical products (for construction sector) [5] from Environdec.. The Ecochain software Mobius version 1.0.23 is used to model the product system. The foreground data is based on the year 2022.

The EPD system boundaries are cradle-to-gate with options, modules A4-A5, B1, C1-C4 and D. The use and end-of-life stages are calculated for the geographical area Europe, since this is the typical market for the product. Operational water and energy use during the use stage are not relevant for this product and are omitted.

Allocation procedures

The principle of modularity shall be maintained. Where processes influence the product's environmental performance during its life cycle, they shall be assigned to the module in the life cycle where they occur (see Figure 1). The sum of the allocated inputs and outputs of a unit process shall be equal to the inputs and outputs of the unit process before allocation. This means no double counting or omission of inputs or outputs through allocation is permitted.

Allocation of co-products

Allocation is avoided when possible, by dividing the unit process to be allocated into different sub-processes that can be allocated to the co-products and by collecting the input and output data related to these sub-processes.

According to PCR 2019:14 v1.2.5, a sub-process system's boundary appears:

- a. each time a product is generated and leaves the specific analysed product system,
- b. each time a waste flow appears and leaves the specific analysed product system,
- c. when product flows are treated in various ways in a process, or
- d. when a material recycling loop occurs outside the own process step

When allocation is necessary, it is based on physical properties when the revenue is low and on economic values in all other cases. Materials flows with specific inherent properties (e.g. biogenic carbon) are allocated according to their physical flows. Avoided impacts from allocated co-products are not declared in module D.

Allocation of waste

The end-of-life system boundary of the product system is set where outputs of the system have reached the end-of-waste state. Examples of these outputs are materials, products or construction elements. This approach ensures that all waste processing during any module of the products system is included up to the system boundary of the respective module. The end-of-waste state is reached when all the following criteria are fulfilled (PCR 2019:14 v1.2.5):



- the recovered material or product (including, e.g., energyware such as fuel, electricity and heat) is commonly used for specific purposes;
- a market or demand, identified for example by a positive economic value, exists for such a recovered material or product;
- the recovered material or product fulfils the technical requirements for the specific purposes for which it is used and meets the existing legislation and standards applicable to its use; and
- the use of the recovered material or product will not lead to overall adverse environmental or human health impacts, which shall be understood as content of hazardous substances below limit values in applicable legislation.

Potential loads and benefits of secondary material, secondary fuel, or recovered energy leaving the product system are declared in module D. When a secondary material or fuel crosses the system boundary, for example at the end-of-waste state substituting another material or fuel in the following product system, the benefits and/or loads will be calculated based on a specified scenario based on current average practice.

Net impacts in module D are calculated by adding all output flows of a secondary material/fuel and subtracting all input flows of this material/fuel from the total product system. The impacts caused by the recycling or recovery process after the end-of-waste state up to the point of function equivalence where the secondary material/fuel substitutes the primary material/fuel are summed up. The impacts from the substituted processes are subtracted from this sum. When the output flow does not reach functional equivalence of the substituting process, a justified value-correction factor should be applied.

At the system boundary, cut-off allocation shall be applied, i.e., all unit processes before the point of end-of-waste shall be assigned to the product system generating the waste and all unit processes after the point of end-of-waste shall be assigned to the subsequent product system (with the exception of co-products in A1-A3). If a waste flow does not fulfil all of the end-of-waste criteria, and thus does not cross the system boundary, all waste treatment processes including those of disposal shall be assigned to the product system generating the waste.

The waste scenarios in this study do not include any incineration, recycling or reuse. The end-of-waste state is not reached by the materials and therefore this study allocated all waste treatment processes to the product system under study.



Table 1. Modules considered in this EPD.

Life cycle stage	Module		Geography	Spec. data	Variation - products	Variation - locations
Production stage	A1	x	Raw material supply	RER		
	A2	x	Transport	RER		
	A3	x	Production	NL	3%*	0%
Construction stage	A4	x	Transport to site	GLO		
	A5	x	Construction - installation process	-		
Use stage	B1	x	Use	-	-	-
	B2	ND	Maintenance	-	-	-
	B3	ND	Repair	-	-	-
	B4	ND	Replacement	-	-	-
	B5	ND	Refurbishment	-	-	-
	B6	ND	Operational energy use	-	-	-
	B7	ND	Operational water use	-	-	-
End-of-life stage	C1	x	Deconstruction demolition	-	-	-
	C2	x	Transport	GLO	-	-
	C3	x	Waste processing	Europe without CH	-	-
	C4	x	Disposal	Europe without CH	-	-
Benefits and loads beyond the system boundaries	D	x	Reuse - Recovery - Recycling potential	RER	-	-

* Specific data was calculated by dividing GWP-GHG emissions of the transport and energy use by the total of A1-A3.




Figure 1. Flowchart of the product system under study, one kilogram of Firetect Graphite sealant fire-rated.



Data quality assessment

It is assumed that the data quality of the information from the processes at the producer is higher than that of the other processes. Therefore, producer specific data is used when possible. These data are recent (2022), complete and based on one year averaged data. The technological coverage and geographical coverage reflect the physical reality of the product. Furthermore, the economic flows approach reality as closely as possible within practically feasible limits for the LCA practitioner.

The time representativeness of the used references for generic data is accurate, since the difference between the reference year (2022) and the time period for which the data is representative (2019) is <3 years.

The geographical coverage of this study is representative of the geographical scope of the production process. Where possible, specific country specific references are selected. Where this is not possible, region-specific references are selected. The quality level ranges from good to very good.

The technological coverage of this study is representative as specific business, product, and process data of the year 2022 are used to model the product system under study. Therefore, the data quality is very good.

The scenarios in this study are currently in use and are representative for one of the most probable alternatives.

Cut-off criteria and assumptions

All inputs and outputs for which data is available are included in the LCA. Data gaps are filled with conservative assumptions and generic data. The cut-off criteria for data gaps is 1% of renewable and nonrenewable energy usage and 1% of the total mass input of that unit process. The total of excluded input per module will not exceed 5% of energy usage and mass input. This LCA uses expert judgement and conservative considerations to determine which inputs comply with these criteria.

Some data gaps were encountered, for example the production of fumed silica, energy use for installation, etc. This section describes how these data gaps were handled.

Fumed silica

There is no database reference for fumed silica available. This study models the main inputs of fumed silica production to replace the missing reference. Since the fumed silica only constitute a small part of the sealant, the use of a proxy does not have a great impact on the reliability of the study.

Fumed silica is produced through pyrogenesis. This entails the heating of silicon tetrachloride, normally through natural gas combustion. The production and combustion of the natural gas is modelled, as well as the silicon tetrachloride production.

Literature about energy consumption of fumed silica production is scarce, so the energy use is based on literature on comparable silica products. Silica can also be produced as silica gel or precipitated silica. According to a report by the European Commission [7], natural gas use for drying silica gel and precipitated silica is 15–24 MJ/kg. Natural gas is also consumed for pyrogenic silica production. It is used for heating hydrogen gas and combustion air, for the evaporation of silicon tetrachloride and for removing residual hydrochloride from the silica surface. Despite the high temperature needed for pyrogenic silica, it does not consume more energy than precipitated silica or silica gel [8]. These two products have a high energy consumption during the necessary drying steps. Thus, this LCA uses a worst case scenario, where the production of fumed (pyrogenic) silica requires 24 MJ/kg.



Exclusion of electricity installation

The installation is typically done with a caulking gun. This can be a manual caulking gun (in 80% of the cases, according to KLF) or an electrical caulking gun (20%). The power of these electric caulking guns is unknown. Typical voltage is 20V, with a battery life of 2 Ah. The ampere is assumed to be 2A, resulting in a power of 0,04 kW. The caulking rate is 1 mm/s at worst. One kilogram of Firetect Graphite sealant fire-rated can be applied to a 20x15mm joint for 2045 mm. This comes to a duration of 0,57 hours per kilogram. The total electricity use is calculated with the following formula. This results in 0,004 kWh per kilogram of Firetect Graphite sealant fire-rated. The impact of this input does not exceed 1% of the energy usage of the installation, and was therefore excluded.

$$\text{Electricity for installation} = \text{duration} \times \text{power} \times \text{share electric installation}$$

Exclusion of installation tools

The actual service life of the tools is unknown, so we assume the tools last 5 years of daily use. This LCA assumes that the tools are used for 8 hours per day, so 14600 hours during its life. The calculated duration of use for the installation of 1 kilogram of Firetect Graphite sealant fire-rated is 0,57 hours. This results in 3,90E-05 units of caulking gun. We assume that the caulking gun, including the Li-ion battery, weighs 5 kg. This results in <1% of the mass and energy use of the installation, since the mass input of construction losses amounts to 0,05 kg. This input was excluded from the calculation.

Exclusion of production waste

The production of the sealant takes place in batches of 1200 kg. The wastage during the production processes is assumed to be minimal, as all materials are used in theory. In practice some materials may spill or stay behind in their casing. This waste is assumed to be negligible (<1%).

Content declaration

The table below shows the material content of 1 kg Firetect Graphite sealant fire-rated.

The packaging per kg is also included in the table. The packaging is consumer packaging, as it contains a sales unit for the final user.

Table 2. Content declaration of 1 kg Firetect Graphite sealant fire-rated.

Material	Weight (kg/kg end product)	Post-consumer recycled material, weight-%	Biogenic material, weight-% and kg C/kg
Aqueous copolymer dispersion from acrylic esters	0,319	-	-
Bio plasticizer	0,038	-	-
Water	0,096	-	-
Dispersing Agent	5,00E-04	-	-
Filler	0,116	-	-
Expandable graphite	0,426	-	-
Thickener	0,005	-	-



Total weight excl. packaging		1,000	
Material	Weight (kg/kg end product)	Weight-% (versus product)	Biogenic material, weight - % and kg C/kg
Cardboard	0,018	1,8%	37,95% / 0,007
PE	0,107	10,7%	0 / 0
Total weight incl. packaging		1,124	
			0,007 kg C/kg

Declaration of material content of SVHC

The product does not contain any substances from the Candidate List of Substances of Very High Concern (SVHC) for authorisation in amounts greater than 0,1% (1000 ppm).



Calculation rules

Production stage (A1-A3)

The materials for 1 kg Firetect Graphite sealant fire-rated are listed in table 1. Lorries of type EURO 6 transport the materials to the production facility. The ingredients are mixed in a dispersing unit at KLF's production site in Gorinchem, the Netherlands. The process consumes grey electricity from natural gas. The electricity was allocated based on the duration of use and power of the dissolver. This was checked against the total energy use of 2022. No production waste occurs.

Construction stage (A4-A5)

The transportation distance is calculated to the storage location in Oslo, Norway. In addition, 300 km of local transport to the consumer is included. The transportation by truck (1277 km) is modelled with a global average reference. This reference includes various lorry types and emission classes. The table below shows the included lorries as well as the characteristics of a container ship (288 km). The installation of the sealant in the construction is usually done manually, therefore energy during installation is excluded. The installation does not require any ancillary materials, water or other resources. There are no known direct emissions during the installation of the sealant. The production, transportation and waste processing of the default production loss of 5% and of packaging waste are modelled in this life cycle stage.

Table 3. Transportation information per transportation type. The values for lorries are based on averages of vehicles of emission type EURO3-EURO6. The values of the ship are based on a global weighted average for container ships.

Type	Capacity utilisation (%)	Volume capacity utilisation factor	Bulk density product (kg/m ³)	Fuel consumption per tkm	Fuel consumption per km
Lorry 3,5-7,5t	Default*	1	1400	0,109-0,111 kg	5,94E-05 kg
Lorry 7,5-16t	Default*	1	1400	0,0472-0,0481 kg	2,57E-05 kg
Lorry 16-32t	Default*	1	1400	0,0366-0,0378 kg	1,86E-05 kg
Lorry >32t	Default*	1	1400	0,0192-0,0196 kg	1,05E-05 kg
Ship	70%	1	1400	0,00252 kg	1,35E-06 kg

* the default value from the ecoinvent reference 'market group for transport, freight, lorry, unspecified | transport, freight, lorry, unspecified | Cutoff, U [GLO]' was used. More information can be found in the ecoinvent v3.8 database.

Table 4. Inputs for the installation of 1 kg Firetect Graphite sealant fire-rated.

Installation input	Quantity
Production losses	5% of all materials listed in table 2

Table 5. Construction waste and processing per material.

Construction waste	Collection	Distance to processing	Total waste	Landfill	Incineration	Recycling
Graphite sealant	Separate	50 km	0,05 kg	0,050 kg	-	-
Cardboard*	Separate	50 km	0,016 kg	1,60E-04 kg	0,016 kg	-
PE*	Separate	50 km	0,094 kg	9,40E-04	0,093 kg	-



* The waste processing of these materials is modelled with a market group reference. The table is based on the most prevalent market, which is DE for cardboard and PE.

Use stage (B1)

The emissions of the Firetect Graphite sealant fire-rated are measured in lab conditions after a period of 28 days. The results can be provided upon request by KLF. This LCA model includes the emissions of VOCs, carcinogenic, mutagenic and reprotoxic (CMR) compounds and aldehydes.

End-of-life stage (C1-C4)

For transport of waste to a waste handling facility, the standard transport distance of 50 km is used, as described in the PCR 2019:14 v1.2.5. Since there is no specific information available from the manufacturer, the standard scenario as prescribed by c-PCR-017 is not used, as the recycling of the sealant is very improbable. The share (10%) of recycling in the default values is replaced by landfilling. It is assumed that the sealant is collected separately.

Table 6. End-of-Life processing of the materials of 1 kg Firetect Graphite sealant fire-rated.

Waste Material	Collection	Transport distance	Landfill (kg)	Incineration (kg)	Recycling (kg)	Reuse (kg)
Graphite sealant	Separate	50 km	100% 1 kg	0%	0%	0%

Loads and benefits outside the system boundaries (D)

No loads or benefits are calculated in module D, as there is no primary material recycled, energy from incineration, or secondary material lost.



Environmental impact per declared unit (1 kg)

Table 8 shows the complete environmental profile of one kilogram Firetect Graphite sealant fire-rated, as applied. The impact assessment results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

The GWP-GHG indicator is required by the PCR v1.2.5 of EPD International. The indicator accounts for all greenhouse gases, with the exception of biogenic carbon dioxide uptake, emissions or storage. It was calculated with the GWP-biogenic and GWP-fossil categories from EF 3.0. In this method, the characterisation factor for biogenic CO₂ is zero. The characterisation factor for fossil CH₄ is 36,8 and for biogenic CH₄ is 34. This impact category is not included in Climate change - total.

Table 8. Environmental impact of 1 kg Firetect Graphite sealant fire-rated as applied, in the core impact categories.

Impact category	A1-A3	A4	A5	B1	C1	C2	C3	C4	D
GWP-total	9,03E-01	1,75E-01	2,83E-01	7,11E-10	0,00E+00	6,76E-03	0,00E+00	5,55E-02	0,00E+00
GWP-f	9,25E-01	1,74E-01	2,47E-01	7,11E-10	0,00E+00	6,70E-03	0,00E+00	5,55E-02	0,00E+00
GWP-b	-3,63E-02	4,77E-04	3,57E-02	0,00E+00	0,00E+00	1,87E-05	0,00E+00	8,74E-05	0,00E+00
GWP-luluc	7,82E-04	1,21E-03	1,12E-04	0,00E+00	0,00E+00	4,74E-05	0,00E+00	1,08E-05	0,00E+00
ODP	5,46E-08	3,68E-08	5,63E-09	0,00E+00	0,00E+00	1,42E-09	0,00E+00	3,21E-09	0,00E+00
AP	3,43E-03	1,03E-03	2,77E-04	0,00E+00	0,00E+00	3,69E-05	0,00E+00	8,96E-05	0,00E+00
EP-fw	2,28E-05	1,99E-06	1,31E-06	0,00E+00	0,00E+00	7,76E-08	0,00E+00	1,71E-07	0,00E+00
EP-m	6,17E-04	3,56E-04	8,14E-05	0,00E+00	0,00E+00	1,31E-05	0,00E+00	3,04E-05	0,00E+00
EP-t	6,88E-03	3,87E-03	7,77E-04	0,00E+00	0,00E+00	1,42E-04	0,00E+00	3,35E-04	0,00E+00
POCP	2,80E-03	1,11E-03	2,72E-04	4,15E-11	0,00E+00	4,10E-05	0,00E+00	1,07E-04	0,00E+00
ADP-mm ²	6,68E-06	5,87E-07	3,82E-07	0,00E+00	0,00E+00	2,28E-08	0,00E+00	3,48E-08	0,00E+00
ADP-f ²	2,22E+01	2,61E+00	1,33E+00	0,00E+00	0,00E+00	1,01E-01	0,00E+00	2,49E-01	0,00E+00
WDP ²	5,48E-01	1,02E-02	2,97E-02	0,00E+00	0,00E+00	3,96E-04	0,00E+00	1,08E-02	0,00E+00
PM	3,32E-08	1,87E-08	3,82E-09	0,00E+00	0,00E+00	7,29E-10	0,00E+00	1,78E-09	0,00E+00
IR ¹	2,33E-02	1,09E-02	2,00E-03	0,00E+00	0,00E+00	4,22E-04	0,00E+00	9,79E-04	0,00E+00
ETP-fw ²	2,47E+01	2,31E+00	1,64E+00	3,41E-10	0,00E+00	8,96E-02	0,00E+00	8,66E-01	0,00E+00
HTP-c ²	3,85E-10	8,40E-11	5,89E-11	1,46E-18	0,00E+00	3,22E-12	0,00E+00	7,76E-12	0,00E+00
HTP-nc ²	8,85E-09	2,43E-09	1,04E-09	9,96E-18	0,00E+00	9,47E-11	0,00E+00	2,29E-10	0,00E+00



SQP ²	4,63E+00	2,32E+00	4,46E-01	0,00E+00	0,00E+00	9,08E-02	0,00E+00	5,93E-01	0,00E+00
------------------	----------	----------	----------	----------	----------	----------	----------	----------	----------

GWP-total = Climate change [kg CO2 eq]; **GWP-f** = Climate change - Fossil [kg CO2 eq]; **GWP-b** = Climate change - Biogenic [kg CO2 eq]; **GWP-luluc** = Climate change - Land use and LU change [kg CO2 eq]; **ODP** = Ozone depletion [kg CFC11 eq]; **AP** = Acidification [mol H+ eq]; **EP-fw** = Eutrophication, freshwater [kg P eq]; **EP-m** = Eutrophication, marine [kg N eq]; **EP-T** = Eutrophication, terrestrial [mol N eq]; **POCP** = Photochemical ozone formation [kg NMVOC eq]; **ADP-mm** = Resource use, minerals and metals [kg Sb eq]; **ADP-f** = Resource use, fossils [MJ]; **WDP** = Water use [m3 depriv.]; **PM** = Particulate matter [disease inc.]; **IR** = Ionising radiation [kBq U-235 eq]; **ETP-fw** = Ecotoxicity, freshwater [CTUe]; **HTP-c** = Human toxicity - cancer; **HTP-nc** = Human toxicity - non-cancer; **SQP** = Land use [Pt] **1**.

This impact category deals mainly with the eventual impact of low dose ionising radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionising radiation from the soil, from radon and from some construction materials is also not measured by this indicator. **2**. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Table 9. The impact of 1 kg Firetect Graphite sealant fire-rated as applied, in the resource use indicators.

Resource use	A1-A3	A4	A5	B1	C1	C2	C3	C4	D
PERE	7,61E-01	4,45E-02	5,57E-02	0,00E+00	0,00E+00	1,73E-03	0,00E+00	4,52E-03	0,00E+00
PERM	2,79E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PERT	1,04E+00	4,45E-02	5,57E-02	0,00E+00	0,00E+00	1,73E-03	0,00E+00	4,52E-03	0,00E+00
PENRE	1,94E+01	2,78E+00	1,42E+00	0,00E+00	0,00E+00	1,07E-01	0,00E+00	2,65E-01	0,00E+00
PENRM	4,53E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
PENRT	2,39E+01	2,78E+00	1,42E+00	0,00E+00	0,00E+00	1,07E-01	0,00E+00	2,65E-01	0,00E+00
SM	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
RSF	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW	1,35E-02	3,45E-04	7,50E-04	0,00E+00	0,00E+00	1,34E-05	0,00E+00	2,63E-04	0,00E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials [MJ]; **PERM** = Use of renewable primary energy resources used as raw materials [MJ]; **PERT** = Total use of renewable primary energy resources [MJ]; **PENRE** = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials [MJ]; **PENRM** = Use of non-renewable primary energy resources used as raw materials [MJ]; **PENRT** = Total use of non-renewable primary energy resources [MJ]; **SM** = Use of secondary material [kg]; **RSF** = Use of renewable secondary fuels [MJ]; **NRSF** = Use of non-renewable secondary fuels [MJ]; **FW** = Use of net fresh water [m3]



Table 10. The impact of 1 kg Firetect Graphite sealant fire-rated as applied, in the waste indicators.

Waste categories	A1-A3	A4	A5	B1	C1	C2	C3	C4	D
HWD	9,49E-06	6,76E-06	1,13E-06	0,00E+00	0,00E+00	2,63E-07	0,00E+00	3,84E-07	0,00E+00
NHWD	8,31E-02	1,78E-01	1,03E-01	0,00E+00	0,00E+00	6,98E-03	0,00E+00	1,00E+00	0,00E+00
RWD	2,15E-05	1,72E-05	2,37E-06	0,00E+00	0,00E+00	6,63E-07	0,00E+00	1,49E-06	0,00E+00

HWD = Hazardous waste disposed [kg]; **NHWD** = Non-hazardous waste disposed [kg]; **RWD** = Radioactive waste disposed [kg]

Table 11. The impact of 1 kg Firetect Graphite sealant fire-rated as applied, in the output flow indicators.

Output flows	A1-A3	A4	A5	B1	C1	C2	C3	C4	D
CRU	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MFR	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MER	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE	0,00E+00	0,00E+00	3,55E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EET	0,00E+00	0,00E+00	6,11E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

CRU = Components for re-use [kg]; **MFR** = Materials for recycling [kg]; **MER** = Materials for energy recovery [kg]; **EEE** = Exported energy, electric [MJ]; **EET** = Exported energy, thermal [MJ]

Table 12. The environmental impact of 1 kg Firetect Graphite sealant fire-rated as applied, on the additional indicator.

Additional indicators	A1-A3	A4	A5	B1	C1	C2	C3	C4	D
GWP-GHG	9,27E-01	1,74E-01	2,64E-01	7,11E-10	0,00E+00	6,70E-03	0,00E+00	5,55E-02	0,00E+00

GWP-GHG = Climate change - greenhouse gases [kg CO₂ eq]



References

- [1] 'ISO 14025: Environmental labels and declarations - Type III environmental declarations - Principles and procedures', International Organization for Standardization, ISO14025:2010.
- [2] 'NEN-EN 15804+A2: Duurzaamheid van bouwwerken - Milieuverklaringen van producten - Basisregels voor de productgroep bouwproducten', NEN-EN 15804:2012+A2:2019.
- [3] PCR 2019:14 Construction products (EN 15804:A2) (1.2.5), IVL Swedish Environmental Research Institute, EPD International Secretariat, June 2022.
- [4] EPD International (2021) General Programme Instructions for the International EPD® System. Version 4.0. www.environdec.com
- [5] EPD Norge (2021) NPCR 009 Part B for Technical – Chemical products for the building- and construction industry. Version 3.0. https://www.epd-norge.no/getfile.php/1321023-1633592287/PCRer/NPCR_009_PART_B_for_technical_chemical_products_15804%20A2%20ver3%20061021.pdf