


# Environmental Product Declaration



In accordance with ISO 14025, EN 15804+A1 and EN 16810 for:

## **Cementi Click hybrid non-PVC flooring - TARKETT**

Programme:	The International EPD® System <a href="http://www.environdec.com">www.environdec.com</a>
Programme operator:	EPD International AB
EPD registration number:	S-P-01503
ECO EPD Ref. number	00000900
Publication date:	2019-05-06
Validity date:	2024-04-18
Geographical scope:	Europe



 **Tarkett**

## General information

### Information about the organization

Owner of the EPD: Tarkett France. Axel ROY, +33 (0)141 204 074, [axel.roy@tarkett.com](mailto:axel.roy@tarkett.com), Tarkett La Défense, 1 Terrasse Bellini 92400 Paris

Description of the organisation: ISO 9001, ISO 14001, ISO 50001, WCM manufacturing site

Name and location of production site: Ronneby, Sweden

### About the company

With an international coverage and a wide range of products, Tarkett has over 130 years of experience in providing integrated solutions for floorings to professionals and end users.

Many of the most important architectural firms in the world and building professionals have chosen Tarkett for the value of its products and for its consultation and service abilities. Therefore, Tarkett floorings and sport surfaces are present in several prestigious architectural reference points. Tarkett offers integrated solutions for floorings, able to meet the particular needs of customers. Our wide range of designs, colors and models provides an infinite series of possibilities, contributing to create a positive environment and a better quality of life for people.

Tarkett operates with the utmost respect for the environment towards the realization of eco-friendly products.

Tarkett's commitment to the environment is woven throughout its business. Cradle-to-Cradle principles are, in fact, the basis of the design and production of every solution. Particularly, the lifecycle analysis is used to continuously improve the production process, and so the products until their use stage, disposal and recycling. The commitment to the environment is also proven by the accession to the Circular Economy 100 program, where Tarkett group, with a network of companies, is working to develop a circular economy model based on the reuse of materials and preservation of natural resources. The development of products that can be reused within internal production cycles, or external ones in case of other individuals, has been an integral part of the business strategy aimed at sustainability for many years. The WCM (World Class Manufacturing) management system has been developed in 2009, and it includes the environmental pillar aimed to the elimination of losses and to the growth of process efficiency.

## Product information

Product name: Cementi Click

Product identification: Cementi Click, Loose-laid panels - Semi-rigid multilayer modular floor (MMF) covering panels with wear resistant top layer

Product description: Cementi Click is a hybrid product, based on a fiber cement board, covered by a digital-printed layer and protective coatings.

The following figure shows the Cementi Click flooring:



**Figure 1 - Cementi Click flooring illustration**

UN CPC code:

Geographical scope: Europe

Range of application:

The product is classified in accordance with EN ISO 10874, EN 685 and in reference to the FCSS (Floor Covering Standard Symbols) to be installed in various areas of application, such as: healthcare, education, commercial, education. The area of use according to the ISO 10874 is heavy (33) for commercial classification.



## LCA information

**Functional unit / declared unit:**

1m<sup>2</sup> of floor covering with a reference service life (RSL) of 1 year and a weight of 12 kg/m<sup>2</sup> for specified characteristics application and use areas according to EN 16511 and EN ISO 10874.

**Reference service life:**

1 year

**Time representativeness:**

2018

**Database(s) and LCA software used:**

SimaPro 8.5

**Description of system boundaries:**

Cradle to grave

## System boundaries


The system boundary is based on the EN 15804 description.

**Production stage : A1 – A3:** includes the provision of all raw materials, transport to the production site and energy consumption during the manufacturing of the product, packaging of final product ,the different air émission,as well as processing of waste generated by the factory.

**Construction stage: A4 – A5:** includes the transport from the factory to the final customer,the installationof the product, as well as all consumables and energy required and processing of waste generated during the installation.

**Use stage B1 – B7:** includes provision and transport of all materials, products and services related to the use phase of the product, as well as their related energy and water consumption, and the processing of any resulting waste.

**End of life stage C1 – C4:** includes provision and transport of all materials, products and services related to the end of life phase of the product, including energy and water consumption, as well as the end of life processing of the product.



## Included/excluded life stages

	Production Stage			Construction Process Stage		Use Stage							End-of-Life Stage			
	Raw material supply (extraction, processing, recycled material)	Transport to manufacturer	Manufacturing	Transport to building site	Installation into building	Use / application	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction / demolition	Transport to EoL	Waste processing for reuse, recovery or recycling	Disposal
Modules	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
Accounted for:	X	X	X	X	X	MND	X	MND	MND	MND	MND	MND	X	X	X	X

X Module included in the study  
MND : Module not declared

**Use stage:** Floor coverings do not contribute to modules B1 and B3 to B7 according to the standard EN 16810.

## Cut-off criteria

The cut-off criteria shall be 1% of renewable and non-renewable primary energy usage and 1% of the total mass of that unit process. The total neglected input flows per module shall be a maximum of 5% of energy usage and mass.

For this study, all input and output flows have been considered at 100%, including raw materials as per the product composition provided by the manufacturer and packaging of raw materials as well as the final product.

## LCA data

As a general rule, specific data derived from specific production processes or average data derived from specific production processes have been used as the first choice as a basis for calculating an EPD. To model the life cycle of the product in question, the software SimaPro 8.5, developed by PRé, has been used in conjunction with the LCA database ecoinvent v3.4.

## Data quality

The objective of this study is to evaluate the environmental impacts generated by the product floor covering Cementi Click throughout its entire life cycle. To this end, ISO 14040, ISO 14044 and EN 15804 have been met regarding the quality of data on different following criteria:

### The time factor, the life cycle inventory data used come from:

- Data collected specifically for this study on Tarkett sites. Data sets are based on 1 year averaged data.

- In the absence of collected data, generic data from the ecoinvent V3.4 cut-off by classification database. This is regularly updated and is representative of current processes

#### Technological Coverage

- Tarkett technologies used for the manufacture methods of the product.
- European technology in the case of use of generic data.

#### Geographical Coverage

- Data comes from partner production sites of Tarkett
- The generic data comes from the ecoinvent database, representative of the European processes.

#### Allocation

The overall values for the factory's material and energy consumptions during a period of one year have been divided by the annual production of each product to supply a value per square meter of flooring produced. All factory data is measured in square meters, and it is assumed that the process consumptions are governed by area of flooring processed rather than mass.

#### Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

## Content declaration

### Product

Characteristics	Nominal Value	Unit	Standard
Product Thickness	7.5	mm	-
Product Weight	12 000	g/m <sup>2</sup>	-
Slip Resistance	≥0.3	-	EN 13893
	R10	-	DIN 51130
Dimension stability	≤0.10 %	-	ISO 23999 EN 434
Light fastness	≥ level 6	-	EN ISO 105-B02

The product is presented in planks of 1235 x 200 mm, or tiles of 920 x 450 mm.

Materials / chemical substances	weight %	Substance concerned with REACH
Fiber cement board	96.58%	/
Green-lignin hydro-tec	1.09%	/
Wear layer coatings	0.94%	/
UV cured coatings	0.78%	/
Glue	0.39%	/
Polyurethane	0.19%	/
Inks	0.04%	/

## Product manufacturing

### Production process

The production of the homogeneous resilient flooring is divided into the following stages:

-

### Production waste

Waste type	Amount	Unit
Non-hazardous waste to landfill	1.39E-01	kg/m <sup>2</sup>
Post-manufacturing internal recycling	1.39E-01	kg/m <sup>2</sup>

NB: Post manufacturing recycling concerns the recycling of the losses inside the plant production. Therefore, there is no end-of-life impact on losses (except the recycling preparation).

### Health, safety and environmental aspects during production

The production site comply with the ISO 14001 Environmental Management System and the ISO 9001 Quality Management System.

### Packaging

Type	Unit	Quantity
Product Packaging Cardboard	kg/m <sup>2</sup> of product	4.45 E-01

## Delivery and installation

### Delivery

The average distribution distance between the factory and the installation site is km. It has been calculated considering the average distance between European countries where Tarkett is selling the Cementi Click product and the factory plant in Müstair (Switzerland). The distribution is made by truck.

### Installation

The product is clicked on the subfloor, then the different parts of the flooring are clicked.

Description	Amount	Unit
Electricity consumption	1.23E-02	kWh/m <sup>2</sup>

### Waste

During the installation approximately 10% of the flooring is lost as off-cuts. All flooring losses are sent to recycling.

### Packaging

50 % of the packaging materials goes to incineration and 50 % goes to landfill

## Use Stage

### Reference Service Life (RSL)

For this product, the stated RSL is 1 year. It should be noted, however, that the service life of a Homogeneous floor covering based upon synthetic thermoplastic polymers may vary depending on the amount and nature of floor traffic and the type and frequency of maintenance. The manufacturer has provided this service life on the basis of his experience of flooring manufacture and supply. This RSL is applicable as long as the product use complies with that defined by ISO 14041 and ISO10 874 in accordance with the product's classification. The service lifetime recommended by Tarkett is 20 years.

### Cleaning and maintenance

The cleaning of the installed floor involves a mechanical cleaning with detergent and the use of a vacuum cleaner.

Description	Amount	Unit
Electricity consumption	4.82E-01	kWh/year/m <sup>2</sup>
Water consumption	3.96E+00	L/year/m <sup>2</sup>
Detergent consumption	8.03E-02	L/year/m <sup>2</sup>



---

### Prevention of structural damage

To avoid excessive wear, usage should be restricted to the stated areas of application as outlined by the norm ISO 10 874.

### End of Life

---

For the purpose of this LCA, it has been assumed that the product is taken back afeter use and sent back to the manufacturing site, where it is re processed in order to reuse the fiber cement board and the backing to build new products. The rest of the product is sent to landfill.

## Environmental performance

### Potential environmental impact

PARAMETER	UNIT	Product stage	Construction stage		Use stage							End of life stage			
		Total Production	Transport	installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction	Transport	Waste processing	Disposal
		A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
Global Warming	kg CO2 eq	1,70E+01	1,78E+00	2,54E+00	MND	4,35E-01	MND	MND	MND	MND	MND	0,00E+00	1,79E+00	0,00E+00	2,14E-02
Ozone Depletion	kg CFC-11 eq	2,06E-06	3,31E-07	2,49E-07	MND	3,55E-08	MND	MND	MND	MND	MND	0,00E+00	3,32E-07	0,00E+00	6,55E-10
Acidification of soil and water	kg SO2 eq.	5,18E-02	5,62E-03	5,99E-03	MND	1,94E-03	MND	MND	MND	MND	MND	0,00E+00	5,70E-03	0,00E+00	1,48E-05
Eutrophication	kg PO4---eq	7,02E-03	9,23E-04	9,26E-04	MND	8,16E-04	MND	MND	MND	MND	MND	0,00E+00	9,46E-04	0,00E+00	1,63E-05
Photochemical ozone creation	kg ethylene	4,08E-03	9,15E-04	5,55E-04	MND	2,10E-04	MND	MND	MND	MND	MND	0,00E+00	9,27E-04	0,00E+00	5,95E-06
Depletion of abiotic resources -elements	kg antimony	2,26E-04	5,55E-06	2,32E-05	MND	8,29E-07	MND	MND	MND	MND	MND	0,00E+00	5,56E-06	0,00E+00	3,28E-09
Depletion of abiotic resources -fossil	MJ. net CV	2,15E+02	2,68E+01	2,48E+01	MND	3,37E+00	MND	MND	MND	MND	MND	0,00E+00	2,69E+01	0,00E+00	5,58E-02



## Use of resources

PARAMETER	UNIT	Product stage	Construction stage		Use stage							End of life stage			
		Total Production	Transport	Installation	Use	Maintenance	Repair	Replacement	refurbishment	Operational energy use	Operational water use	Deconstruction	Transport	Waste processing	Disposal
		A1-A3	A4	A5	B1	B2.	B3	B4	B5	B6	B7	C1	C2.	C3	C4
Renewable primary energy excl. RM	MJ. net CV	2,96E+01	4,00E-01	3,04E+00	MND	1,51E+00	MND	MND	MND	MND	MND	0,00E+00	4,01E-01	0,00E+00	2,13E-03
Renewable primary energy used as RM	MJ. net CV	1,88E+01	0,00E+00	1,88E+00	MND	8,35E-01	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total renewable primary energy	MJ. net CV	4,84E+01	4,00E-01	4,92E+00	MND	2,35E+00	MND	MND	MND	MND	MND	0,00E+00	4,01E-01	0,00E+00	2,13E-03
Non renewable primary energy excl. RM	MJ. net CV	2,23E+02	2,74E+01	2,58E+01	MND	5,68E+00	MND	MND	MND	MND	MND	0,00E+00	2,76E+01	0,00E+00	6,05E-02
Non renewable primary energy used as RM	MJ. net CV	1,24E+01	0,00E+00	1,24E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total non renewable primary energy	MJ. net CV	2,36E+02	2,74E+01	2,71E+01	MND	5,68E+00	MND	MND	MND	MND	MND	0,00E+00	2,76E+01	0,00E+00	6,05E-02
Use of secondary material	kg	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of renewable secondary fuels	MJ. net CV	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of non renewable secondary fuels	MJ. net CV	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Net use of fresh water	m3	1,55E-01	5,16E-03	1,68E-02	MND	1,43E-02	MND	MND	MND	MND	MND	0,00E+00	5,18E-03	0,00E+00	7,17E-05



## Waste production and output flows

PARAMETER	UNIT	Product stage	Construction stage		Use stage							End of life stage			
		Total Production	Transport	Installation	Use	Maintenance	Repair	Replacement	refurbishment	Operational energy use	Operational water use	Deconstruction	Transport	Waste processing	Disposal
		A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
Hazardous waste disposed	kg	7,88E-02	1,62E-02	1,72E-02	MND	1,79E-02	MND	MND	MND	MND	MND	0,00E+00	1,63E-02	0,00E+00	5,18E-05
Non-hazardous waste disposed	kg	3,22E+00	1,43E+00	1,99E+00	MND	1,31E-01	MND	MND	MND	MND	MND	0,00E+00	1,43E+00	0,00E+00	2,50E-01
Radioactive waste disposed	kg	1,05E-03	1,88E-04	1,29E-04	MND	3,41E-05	MND	MND	MND	MND	MND	0,00E+00	1,89E-04	0,00E+00	4,07E-07
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy (electricity)	MJ	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy (steam)	MJ	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00



## Programme-related information and verification

The EPD owner has the sole ownership, liability, and responsibility for the flooring EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of floor products may not be comparable if they do not comply with EN 15804 and EN 16810.

<b>Programme:</b>	<p>The International EPD® System</p> <p>EPD International AB Box 210 60 SE-100 31 Stockholm Sweden</p> <p><a href="http://www.environdec.com">www.environdec.com</a> <a href="mailto:info@environdec.com">info@environdec.com</a></p>
<b>EPD registration number:</b>	S-P-01503
<b>ECO EPD Ref. number:</b>	00000900
<b>Published:</b>	2019-05-06
<b>Valid until:</b>	2024-04-18
<b>Product Category Rules:</b>	PCR 2012:01 version 2.2 and Sub-PCR-F Resilient, textile and laminate floor coverings (EN 16810)
<b>Product group classification:</b>	UN CPC APE/NAF - 2223Z
<b>Reference year for data:</b>	2018
<b>Geographical scope:</b>	Europe

CEN standard EN 15804 and EN 16810 serve as the Core Product Category Rules (PCR)
Product category rules (PCR): EN 15804 and EN 16810
Independent third-party verification of the declaration and data, according to ISO 14025:2006: <input type="checkbox"/> EPD process certification <input checked="" type="checkbox"/> EPD verification
Third party verifier: Damien PRUNEL, BUREAU VERITAS LCIE
Procedure for follow-up of data during EPD validity involves third party verifier: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

## References

**General Programme Instructions of the International EPD® System. Version 3.0.**

PCR 2012:01 version 2.2

### Contact information:

	<p><b>Programme operator:</b> EPD International AB info@environdec.com</p>
	<p><b>Author and Owner of the Declaration</b> TARKETT Tarkett La Défense. 1 Terrasse Bellini 92400 Paris</p> <p>Tel +33 (0)1 41 20 40 74 Mail <a href="mailto:axel.roy@tarkett.com">axel.roy@tarkett.com</a> Web <a href="http://www.tarkett.com">www.tarkett.com</a></p>
	<p><b>Reviewer</b> BUREAU VERITAS LCIE 170 rue de Chatagnon ZI Centr'alp - 38430 Moirans - FRANCE</p> <p>Tel +33 (0)4 76 07 36 42 Mail <a href="mailto:damien.prunel@fr.bureauveritas.com">damien.prunel@fr.bureauveritas.com</a> Web <a href="http://www.codde.fr">www.codde.fr</a></p>

