

Environmental Product Declaration



In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

Copper Press Fittings V-Profile, a-collection

from

Ahlsell AB



Programme	EPD International AB
Programme operator	The International EPD® System
EPD registration number	S-P-11001
Publication date	2023-12-04
Valid until	2028-12-03

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com



General Information

Programme information	
Programme	The International EPD® System
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden
Website	www.environdec.com
E-mail	info@environdec.com

Accountabilities for PCR, LCA and independent, third-party verification	
Product Category Rules (PCR)	Product Category Rules (PCR): Construction products, 2019:14, Version 1.3.1
Life Cycle Assessment (LCA)	Carbonzero AB
Third-party verification:	<p>Independent third-party verification of the declaration and data, according to ISO 14025:2006:</p> <p><input checked="" type="checkbox"/> EPD process certification</p> <p>Vladimír Kocí, LCA Studio</p>  <p>Approved by: The International EPD® System</p>
Procedure for follow-up of data during EPD validity involves third party verifier: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

Company information	
Owner of the EPD	Ahlsell AB
Contact	Andrea Wästlund
Description of the organisation	Ahlsell AB is present where people reside, work, and live their lives. Ahlsell AB is currently the Nordic region's leading community-building distributor of installation products, tools, and supplies for installation, construction, real estate management, industrial and power companies, and the public sector. With around 7,500 employees, 300 stores, ecommerce, and four central warehouses, we are working daily to achieve our vision of building a more sustainable society.
Product-related or management system-related certifications:	ISO 9001 & ISO 14001
Name and location of production site(s):	Name of plant: Manufacturing plant Location: Sweden

Product information	
Product name(s)	22 A-PRESS CU TEE TYPE V. COPPEREND
Product description:	Press fittings A-press V profile. The press pipe parts are made of copper and dezincification-resistant brass CW511L which meets the Housing Authority's requirements for lead leakage. O-ring with leak indication approved according to SP method 5060 which is based on the German test method DVGW W534.
RSL	50 years
UN CPC code	41516 - Tubes, pipes and tube or pipe fittings, of copper

LCA information	
Functional unit / declared unit	1 kg of Copper Press Fittings V-Profile
Time representative-ness	Data obtained refer to the year 2022
System Boundary	The system boundaries are set to be "cradle-to-gate" with modules A4, C1-C4, and D for end-of-life.
Database(s) and LCA software used	Eando X version 1.01

System diagram

D Benefits and loads beyond the system boundary

A1	Raw material supply	This module considers the extraction and processing of all raw materials, energy, and transportation which occur upstream to the studied manufacturing process, including packaging material.
A2	Transport to the manufacturer	The raw materials are transported to the manufacturing site.
A3	Manufacturing	This module includes all resources used to produce and waste produced. This also includes additives and packaging material.
A4	Transport	Transportation from the manufacturing site to distribution centre and then from the distribution centre to the building site is included.
	Transport Scenario	Truck: 200km
A5	Construction installation	This stage is not declared.
B1-B7	Use stage	This stage is not declared.
C1	Deconstruction/Demolition	This stage includes the de-construction and/or demolition of the building. This is not relevant as the product included in this study is not used in the construction process.
C2	Transport	This stage represents the transport distance to the waste processing facility.
C3	Waste processing	This stage includes any waste treatment needed.
	EOL Scenario	Landfill 9.81%. Incineration 1.88%. Recycling 88.3%.
C4	Final disposal	This includes any material that is landfilled.
D	Benefits	Emission credits obtained from energy recovery and/or recycling materials

Modules declared, geographical scope, share of specific data (in GWP-GHG results) and data variation (in GWP-GHG results):

	Product stage		Assembly stage		Use stage						End of life stage				Benefits & loads beyond system boundary		
	Raw Materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery - Recycling-potential
	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Declared	X	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X
Geography	CN	GL	SE	SE	-	-	-	-	-	-	-	SE	SE	SE	SE	SE	SE
Specific data used	Factory supplied specific data for A1- A3		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Variation-Products	Averaged		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Variation-Sites	0 %		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Content Information

Product Components	Weight, kg	Post-consumer material, weight-%	Biogenic material, weight-% and kg C/kg
Rubber	0.018	0.000	0.000
Plastic	0.001	0.000	0.000
Metal	0.981	55.000	0.000
Total	1.000	53.960	0.000

Packaging Materials	Weight, kg	Weight-% (versus the product)	Weight biogenic carbon, kg C/kg
Polyethylene (PE)	0.003	0.300	0.000
Carton	0.020	2.000	0.009
EU pallet normal	0.006	0.625	0.003
Total	0.029	2.925	0.011

Dangerous substances from the candidate list of SVHC for Authorisation	EC No.	CAS No.	Weight-% per functional or declared unit

At the date of issue of this declaration, there is no "Substance of Very High Concern" (SVHC) in concentration above 0.1% by weight, and neither does the packaging, following the European REACH regulation (Registration, Evaluation, Authorization and Restriction of Chemicals)

Environmental Information

Potential environmental impact – indicators according to EN 15804+A2

Results per functional unit: 1 kg								
Indicator	Unit	A1 - A3	A4	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	5.84e+0	1.78e-2	0.00e+0	3.57e-3	3.15e-2	4.53e-3	-3.91e+0
GWP-fossil	kg CO ₂ eq	5.83e+0	1.71e-2	0.00e+0	3.42e-3	3.74e-2	4.59e-3	-3.90e+0
GWP-biogenic	kg CO ₂ eq	5.05e-3	7.30e-4	0.00e+0	1.46e-4	-5.87e-3	-5.68e-5	2.58e-3
GWP-luluc	kg CO ₂ eq	1.43e-2	4.72e-7	0.00e+0	9.44e-8	2.75e-6	4.66e-6	-1.11e-2
ODP	kg CFC-11 eq	2.01e-8	1.03e-15	0.00e+0	2.06e-16	2.57e-14	7.57e-15	-1.60e-8
AP	mole H ⁺ eq	1.70e-1	1.47e-4	0.00e+0	2.94e-5	8.16e-6	1.47e-5	-1.34e-1
EP-freshwater	kg P eq	9.15e-3	2.20e-9	0.00e+0	4.40e-10	7.54e-9	4.15e-9	-7.41e-3
EP-marine	kg N eq	9.90e-3	7.32e-5	0.00e+0	1.46e-5	2.63e-6	3.70e-6	-7.29e-3
EP-terrestrial	mole N eq	1.23e-1	8.02e-4	0.00e+0	1.60e-4	3.52e-5	4.06e-5	-9.14e-2
POCP	kg NMVOC eq	3.60e-2	1.38e-4	0.00e+0	2.76e-5	7.50e-6	1.16e-5	-2.71e-2
ADP-minerals & metals	kg Sb eq	3.84e-3	1.14e-10	0.00e+0	2.28e-11	2.26e-10	1.26e-10	-3.11e-3
ADP-fossil	MJ	6.98e+1	2.46e-1	0.00e+0	4.92e-2	5.73e-2	6.86e-2	-4.75e+1
WDP	m ³	4.25e+0	7.70e-5	0.00e+0	1.54e-5	3.71e-3	-6.23e-5	-3.17e+0
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption							

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator

Use of resources

Results per functional unit: 1 kg								
Indicator	Unit	A1 - A3	A4	C1	C2	C3	C4	D
PERE	MJ	1.77e+1	1.35e-3	0.00e+0	2.70e-4	1.34e-2	6.16e-3	-1.19e+1
PERM	MJ	0.00e+0						
PERT	MJ	1.41e+1	1.35e-3	0.00e+0	2.70e-4	1.34e-2	6.16e-3	-8.96e+0
PENRE	MJ	4.69e+1	2.46e-1	0.00e+0	4.92e-2	5.73e-2	6.86e-2	-2.89e+1
PENRM	MJ	1.67e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	-1.35e+0
PENRT	MJ	7.01e+1	2.46e-1	0.00e+0	4.92e-2	5.73e-2	6.86e-2	-4.77e+1
SM	kg	0.00e+0						
RSF	MJ	1.43e+1	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	-1.16e+1
NRSF	MJ	0.00e+0						
FW	m3	8.83e-2	2.06e-6	0.00e+0	4.12e-7	9.28e-5	7.72e-7	-6.49e-2
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water							

* This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO₂ is set to zero.

Additional voluntary indicators

Results per functional unit: 1 kg								
Indicator	Unit	A1 - A3	A4	C1	C2	C3	C4	D
GWP-GHG	kg CO ₂ eq	5.79e+0	1.75e-2	0.00e+0	3.51e-3	3.74e-2	4.43e-3	-3.85e+0
EP	kg PO ₄ eq	3.06e-2	0.00e+0	0.00e+0	0.00e+0	1.16e-6	1.30e-6	-2.48e-2
Acronyms	GWP-GHG global warming potential - greenhouse gases; EP eutrophication potential							

Additional voluntary indicators

This indicator supports comparability with EPDs based on the previous version of EN 15804 (EN 15804:2012+A1:2013).

Waste and output flows

Results per functional unit: 1 kg								
Indicator	Unit	A1 - A3	A4	C1	C2	C3	C4	D
HWD	kg	9.73e-10	6.12e-14	0.00e+0	1.22e-14	2.00e-13	5.66e-12	-1.17e-9
NHWD	kg	2.64e+0	9.34e-6	0.00e+0	1.87e-6	1.53e-2	9.81e-2	-2.13e+0
RWD	kg	4.28e-4	8.88e-8	0.00e+0	1.78e-8	1.60e-6	7.98e-7	-1.62e-4
Acronyms	HW Hazardous waste disposed; NHW Non-hazardous waste disposed; RW Radioactive waste disposed							

Output flows

Results per functional unit: 1 kg								
Indicator	Unit	A1 - A3	A4	C1	C2	C3	C4	D
CRU	kg	1.43e+1	0.00e+0	0.00e+0	0.00e+0	0.00e+0	0.00e+0	-1.16e+1
MFR	kg	0.00e+0						
MER	kg	0.00e+0						
EEE	MJ	0.00e+0	0.00e+0	0.00e+0	0.00e+0	5.12e-2	0.00e+0	0.00e+0
EET	MJ	0.00e+0	0.00e+0	0.00e+0	0.00e+0	9.28e-2	0.00e+0	0.00e+0
Acronyms	CRU Components for reuse; MFR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy							

Product Table

Name	Weight, kg	Unit
22 A-PRESS CU TEE TYPE V. COPPEREND	0.049	pc
15 A-PRESS CU TEE TYPE V. COPPEREND	0.028	pc
18 COUPLING CUVA-PRESS	0.361	pc
12 COUPLING CUVA-PRESS	0.154	pc
15x10 REDUCER CUVA-PRESS	0.095	pc
28 COUPLING CUVA-PRESS	0.039	pc
15 COUPLING CUVA-PRESS	0.226	pc
22 COUPLING CUVA-PRESS	0.029	pc
22X15X22 A-PRESS CU TEE TYPE V. COPPEREND	0.036	pc
12x10 REDUCER CUVA-PRESS	0.065	pc
12 SLIP COUPLING CUVA-PRESS	0.170	pc
15 SLIP COUPLING CUVA-PRESS	0.248	pc
42 SLIP COUPLING CUVA-PRESS	0.076	pc
18 SLIP COUPLING CUVA-PRESS	0.362	pc
54 COUPLING CUVA-PRESS	0.094	pc
28 SLIP COUPLING CUVA-PRESS	0.073	pc
35 SLIP COUPLING CUVA-PRESS	0.060	pc
42 COUPLING CUVA-PRESS	0.068	pc
35 COUPLING CUVA-PRESS	0.049	pc
22 SLIP COUPLING CUVA-PRESS	0.056	pc

Name	Weight, kg	Unit
22 ELBOW 90° W. PLAIN END CUVA-PRESS	0.430	pc
12 ELBOW 90° WITH PLAIN END CUVA-PRESS	0.132	pc
18 ELBOW 90° WITH PLAIN END CUVA-PRESS	0.261	pc
15 ELBOW 90° WITH PLAIN END CUVA-PRESS	0.175	pc
54 SLIP COUPLING CUVA-PRESS	0.093	pc
28 ELBOW 90° W. PLAIN END CUVA-PRESS	0.628	pc
35 ELBOW 90° W. PLAIN END CUVA-PRESS	0.069	pc
42 ELBOW 90° W. PLAIN END CUVA-PRESS	0.076	pc
54 ELBOW 90° W. PLAIN END CUVA-PRESS	0.077	pc
12 ELBOW 90° CUVA-PRESS	0.081	pc
15 ELBOW 45° WITH PLAIN END CUVA-PRESS	0.113	pc
22 ELBOW 90° CUVA-PRESS	0.095	pc
12 ELBOW 45° WITH PLAIN END CUVA-PRESS	0.110	pc
15 ELBOW 90° CUVA-PRESS	0.104	pc
42 ELBOW 90° CUVA-PRESS	0.102	pc
28 ELBOW 90° CUVA-PRESS	0.091	pc
35 ELBOW 90° CUVA-PRESS	0.094	pc
18 ELBOW 90° CUVA-PRESS	0.084	pc
54 ELBOW 90° CUVA-PRESS	0.113	pc
18 ELBOW 45° WITH PLAIN END CUVA-PRESS	0.114	pc

Product Table

Name	Weight, kg	Unit
54 ELBOW 45° W. PLAIN END CUVA-PRESS	0.135	pc
28 ELBOW 45° WITH PLAIN END CUV. A-PRESS	0.131	pc
28 ELBOW 45° CUVA-PRESS	0.177	pc
15 ELBOW 45° CUVA-PRESS	0.163	pc
22 ELBOW 45° CUVA-PRESS	0.173	pc
18 ELBOW 45° CUVA-PRESS	0.153	pc
35 ELBOW 45° WITH PLAIN END CUV. A-PRESS	0.131	pc
42 ELBOW 45° WITH PLAIN END CUV. A-PRESS	0.145	pc
12 ELBOW 45° CUVA-PRESS	0.128	pc
22 ELBOW 45° WITH PLAIN END CUV. A-PRESS	0.110	pc
22 TEE CUVA-PRESS	0.359	pc
12TEE CUVA-PRESS	0.305	pc
54 ELBOW 45° CUVA-PRESS	0.230	pc
28 TEE CUVA-PRESS	0.462	pc
15 PIPE BRIDGE CUV. A-PRESS 1 MUFF	0.243	pc
12 PIPE BRIDGE CUV. A-PRESS 1 MUFF	0.233	pc
35 ELBOW 45° CUVA-PRESS	0.197	pc
15 TEE CUVA-PRESS	0.337	pc
42 ELBOW 45° CUVA-PRESS	0.226	pc
18 TEE CUVA-PRESS	0.352	pc

Name	Weight, kg	Unit
15x12 TEE CUVA-PRESS	0.040	pc
35 TEE CUVA-PRESS	0.485	pc
15X15X12 TEE CUVA-PRESS	0.049	pc
15x22 TEE CUVA-PRESS	0.052	pc
18x15x15 TEE CUVA-PRESS	0.109	pc
15x12x12 TEE CUVA-PRESS	0.031	pc
18x12 TEE CUVA-PRESS	0.072	pc
12x15 TEE CUVA-PRESS	0.550	pc
54 TEE CUVA-PRESS	0.549	pc
42 TEE CUVA-PRESS	0.527	pc
22X18X15 T-PIECE CUVA-PRESS	0.042	pc
22x15x15 TEE CUVA-PRESS	0.029	pc
18X15 TEE CUVA-PRESS	0.160	pc
22x18 TEE CUVA-PRESS	0.052	pc
22x22x15 TEE CUVA-PRESS	0.053	pc
22x22x18 T-PIECE CUVA-PRESS	0.058	pc
18x18x15 TEE CUVA-PRESS	0.260	pc
22x15 TEE CUVA-PRESS	0.033	pc
22x18x18 TEE CUVA-PRESS	0.044	pc
22x12 TEE CUVA-PRESS	0.026	pc

Product Table

Name	Weight, kg	Unit
28x22 TEE CUVA-PRESS	0.141	pc
28x22x22 TEE CUVA-PRESS	0.120	pc
28x15x22 TEE CUVA-PRESS	0.085	pc
22x28 TEE CUVA-PRESS	0.083	pc
35x22 TEE CUVA-PRESS	0.024	pc
35x22x28 TEE CUVA-PRESS	0.020	pc
35x15 TEE CUVA-PRESS	0.015	pc
28X28X15 TEE CUVA-PRESS	0.208	pc
28X28X22 TEE CUVA-PRESS	0.222	pc
28x15 TEE CUVA-PRESS	0.115	pc
54x42x42 TEE CUVA-PRESS	0.001	pc
42x35 TEE CUVA-PRESS	0.037	pc
35x28x28 TEE CUVA-PRESS	0.032	pc
54x35 TEE CUVA-PRESS	0.000	pc
35x28 TEE CUVA-PRESS	0.042	pc
54x22 TEE CUVA-PRESS	0.000	pc
42x28 TEE CUVA-PRESS	0.122	pc
54X28 TEE CUVA-PRESS	0.000	pc
42x35x35 TEE CUVA-PRESS	0.175	pc
42x22 TEE CUVA-PRESS	0.079	pc

Name	Weight, kg	Unit
35x28 REDUCER CUVA-PRESS	0.000	pc
18x15 REDUCER CUVA-PRESS	0.003	pc
22x18 REDUCER CUVA-PRESS	0.000	pc
54x42 REDUCER CUVA-PRESS	0.001	pc
22x15 REDUCER CUVA-PRESS	0.004	pc
15x12 RED. WITH PLAIN END CUVA-PRESS	0.001	pc
28x22 REDUCER CUVA-PRESS	0.000	pc
54x42 TEE CUVA-PRESS	0.001	pc
42x35 REDUCER CUVA-PRESS	0.001	pc
15x12 REDUCER CUVA-PRESS	0.001	pc
28x15 RED. CUVW. PLAIN END A-PRESS	0.230	pc
22x18 RED. WITH PLAIN END CUVA-PRESS	0.071	pc
35x22 RED. WITH PLAIN END CUVA-PRESS	0.074	pc
18x12 RED. CUVW. PLAIN END A-PRESS	0.003	pc
28x22 RED. CUVW. PLAIN END A-PRESS	0.129	pc
28x18 RED. WITH PLAIN END CUVA-PRESS	0.059	pc
18x15 RED. WITH PLAIN END CUVA-PRESS	0.004	pc
35x28 RED. WITH PLAIN END CUVA-PRESS	0.132	pc
42x22 RED. WITH PLAIN END CUVA-PRESS	0.192	pc
22x15 RED. CUVW. PLAIN END A-PRESS	0.094	pc

Product Table

Name	Weight, kg	Unit
42x35 RED. WITH PLAIN END CU V A-PRESS	0.094	pc
54x35 RED. WITH PLAIN END CU V A-PRESS	0.106	pc
18 CAP CU V A-PRESS	0.193	pc
12 CAP CU V A-PRESS	0.158	pc
28 CAP CU V A-PRESS	0.337	pc
35 CAP CU V A-PRESS	0.437	pc
42x28 RED. WITH PLAIN END CU V A-PRESS	0.082	pc
54x42 RED. WITH PLAIN END CU V A-PRESS	0.141	pc
22 CAP CU V A-PRESS	0.243	pc
15 CAP CU V A-PRESS	0.175	pc
54 CAP CU V A-PRESS	0.215	pc
28 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.044	pc
22 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.032	pc
18 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.855	pc
16x15 REDUCER CU V A-PRESS	0.260	pc
15 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.444	pc
35 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.034	pc
42 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.045	pc
42 CAP CU V A-PRESS	0.156	pc
54 O-RING CULBP EPDM BLACK A-PRESS 5PCS/BAG	0.063	pc

Name	Weight, kg	Unit
22 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.071	pc
42 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.103	pc
35 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.085	pc
18 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.060	pc
A-PRESS COPPER V PRESS COUPLING. 35x18x35mm	0.196	pc
12 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.051	pc
28 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.105	pc
54 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.123	pc
15 O-RING CULBP VITON SOLAR GREEN. A-PRESS 5 PCS/BAG	0.062	pc

Additional information

The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins, and/or risks. It is advised not to use the results of modules A1-A3 (A1-A5 for services) without considering the results of module C.

The end-of-life reflects the Swedish market, where 1 % of ferrous metallic waste is landfilled, and 99 % recycled, a wastage of 10 % is considered during the recycling process. The other materials' EoL scenarios are as per SCB data for 2020. For the credit for recovered material (module D), EU datasets were used.

Data quality: All datasets used came from reputable databases Sphera Managed LCA Content (MLC) (fka GaBi database) and EcoInvent, with good technological representativeness. Therefore, it could be considered good.

Allocation: No co-product allocation has been applied since no co-products are generated, and therefore allocation has not been relevant.

Cut-off Criteria: The general rules for the exclusion of inputs and outputs follow the requirements in EN15804+A2.

References

- EN 15804:2012+A2 Sustainability of construction works – Environmental product declaration – Core rules for the product category of construction products
- EPD International (2021) General Programme Instructions of the International EPD® System, version 4.0
- PCR 2019:14 PCR 2019:14. v1.3.1. Construction products (EN 15804: A2)
- SCB (2023) https://www.statistikdatabasen.scb.se/pxweb/en/ssd/START_MI_MI0305/MI0305T003/table/tableViewLayout1/
- ISO 14025:2006 International Standard ISO 14025 – Environmental labels and declarations – Type III environmental declarations – Principles and procedures
- ISO 14040:2006 International Standard ISO 14040: Environmental Management – Life cycle assessment – Principles and framework. Second edition 2006-07-01.
- ISO 14044:2006 International Standard ISO 14044: Environmental Management – Life cycle assessment – Requirements and Guidelines.

Contact Info

EPD owner:	 a-collection Ahlsell AB Email: andrea.wastlund@ahlsell.se Telephone: +46 8 685 70 00 Adress: SE-117 98 Stockholm, Sweden
LCA author:	 CARBONZERO Carbonzero AB Email: info@eando.se Telephone: +46 4 317 07 07 Adress: SE-262 32 Ängelholm, Sweden
Third party verifier:	 LCA Studio Vladimír Koci Email: vladimir.koci@lcastudio.cz Telephone: +420 608 055 972 Adress: LCA Studio, Šárecká 1962/5, 160 00 Praha 6
Program operator:	 EPD EPD International AB Email: info@environdec.com Telephone: +46 (0)73 311 30 20 Adress: SE-11427 Stockholm, Sweden