





# ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025 for

# Mapedeck Soft Design System



Programme: The International EPD® System; www.environdec.com Programme operator:

**EPD International AB** 

EPD registration number:

Publication date: Valid until:

Geographical scope:

S-P-01382

date: 2019-06-10 2024-06-09

International







### **1. COMPANY DESCRIPTION / GOAL & SCOPE**

Founded in 1937 in Milan, Italy, Mapei produces adhesives and complementary products for laying all types of floor, wall and coating materials, and also specializes in other chemical products used in the building industry, such as waterproofing products, specialty mortars, admixtures for concrete, products for underground constructions and for the restoration of concrete and historical buildings.

There are currently 85 subsidiaries in the Mapei Group, with a total of 80 production facilities located around the world in 35 different countries and in 5 different continents. Mapei also has 31 central laboratories. Most locations are ISO 9001 and ISO 14001 or EMAS-certified.

Mapei's strategy of internationalization is based on two main objectives: being closer to local needs and lowering transportation costs. With the declared objective of being close to buyers and clients, Mapei's presence in the five continents enables the company to comply with the requirements of each location, and to use only locally-based managers and qualified personnel, without changing the approach of Mapei.

Mapei invests 12% in its company's total work-force and 5% of its turnover in Research & Development; in particular, 70% of its R&D efforts are directed to develop eco-sustainable and environmentally friendly products, which give important contribution to all major green rating systems for eco-sustainable buildings such as LEED and BREEAM.

Furthermore, Mapei has developed a sales and technical service network with offices all over the world and offers an efficient Technical Assistance Service that is valued by architects, engineers, contractors and owners.

The goal of the study is to provide necessary data and documentation to produce an EPD according to the requirements of PCR Environdec (version 2.2, 2017-05-30) under EN 15804:2014 and to have more comprehension about the environmental impacts related to the components included in **Mapedeck Soft Design System** manufactured in Mapei S.p.A. located in Robbiano di Mediglia (Italy), including packaging of the finished products.

Target audiences of the study are customers and other parties with an interest in the environmental impacts of the **Mapedeck Soft Design System**.

This analysis shall not support comparative assertions intended to be disclosed to the public.

## 2. PRODUCT DESCRIPTION

The products included in Mapedeck Soft Design System are the following:

**Mapedeck Primer 200** is a two-component, adhesion promoter for polyurethane systems. It's packaged in 5,5 kg canister (A+B).

**Mapedeck Flexiscreed** is a two-component, viscoelastic polyurethane base layer for levelling off internal and external bridge decks on ships. It's packaged in 17 kg cans (A+B).

Maperubber Black 25 is a granulated rubber filler. It's packaged in 25 kg bags. Mapedeck Soft Design is a two-component, seamless "elastic" self-levelling resin coating for internal and external bridge decks on ships. It's packaged in 19 kg cans (A+B).

**Maperubber EPDM 15** is a granulated EPDM filler used as decorative filler material. It's packaged in 25 kg bags.

**Mapedeck Finish 111 TSR** is a two-component, aliphatic, matt polyurethane finishing product in water dispersion; available in transparent or various colours and with a smooth or anti-skid finish. It's packaged in 6 kg cans and can be used in alternative to **Mapedeck Wax**.

**Mapedeck Wax** is a one-component, transparent aliphatic polyurethane finish in water dispersion. It's resistant to UV rays and yellowing. It's packaged in 5 kg cans and can be used in alternative to **Mapedeck Finish 111 TSR**.

Mapedeck Flexiscreed, Mapedeck Soft Design, Mapedeck Finish 111 TSR are suitable for marine equipment in compliance with the Marine Equipment Directive (MED) 96/98/EC and subsequent amendments.







### 3. CONTENT DECLARATION

The following table shows the composition of the system studied:

Table 1: Mapedeck Soft Design System		
Component	Consumption (kg/m²)	
Mapedeck Primer 200	0,1	
Mapedeck Flexiscreed	6,3 (7 mm thickness)	
Maperubber Black 25	2,45 (7 mm thickness)	
Mapedeck Soft Design	4,05 (3 mm thickness)	
Maperubber EPDM 15	0,5	
Mapedeck Finish 111 TSR	0,1	
Mapedeck Wax*	0,04	
Mapedeck Soft Design System (TOT)	13,50/13,44**	

\*Can be used **instead of** Mapedeck Finish 111 TSR

\*\*According to the finish used (i.e. 14,34 kg/m<sup>2</sup> with the use of Mapedeck Wax)

For further infomation consult the TDS (Technical Data Sheet).

The products contain neither carcinogenic substances nor substances of very high concern (SVHC) on the REACH Candidate List published by the European Chemicals Agency, in a concentration higher than 0,1 % (by unit weight).

### 4. DECLARED UNIT AND REFERENCE SERVICE LIFE

#### The declared unit is 1 kg of product, packaging included.

Packaging materials include:

- PP (Polypropylene)
- PE (Polyethylene)
- Carboard
- · LDPE (Low Density Polyethylene)

• Wood

According to the system boundary applied the RSL is not specified in this study.



### 5. SYSTEM BOUNDARIES AND ADDITIONAL TECHNICAL INFORMATION

The approach is "cradle to gate".

The following modules have been considered:

 A1, A2, A3 (Product stage): extraction and transport of raw materials and packaging, production process.



A brief description of production process is the following:

The production process starts from raw materials, that are purchased from external and intercompany suppliers and stored in the plant. Bulk raw materials are stored in specific silos and added automatically in the production mixer, according to the formula of the product. Other raw materials, supplied in bags or big bags, are stored in their warehouse and added automatically or manually in the mixer. During the production of the powder, all the components are mechanically mixed in batches. Raw materials of latexes are mixed, properly diluted and packed into drums. The semi-finished products are then packaged, put on wooden pallets, covered by stretched hoods and stored in the Finished Products' warehouse. The quality of final products is controlled before the sale.





Figure 1: Production process detail





**EPD**<sup>®</sup>

### 6. CUT-OFF RULES & ALLOCATION

Criteria for the exclusion of inputs and outputs (cut-off rules) in the LCA, information modules and any additional information are intended to support an efficient calculation procedure. They are not applied in order to hide data.

The following procedure is applied for the exclusion of inputs and outputs:

- All inputs and outputs to a unit process, for which data are available, are included in the calculation.
- Cut-off criteria, where applied, are described in Table 3.

Input flows are covered for over 99% of the formulas.

Table 3: Cut-off criteria			
Process excluded from the study	Cut-off criteria	Quantified contribution from process	
A3: production (auxiliary materials)	Less than 10 <sup>-5</sup> kg/kg of finished product	Sensitivity study demonstrates a relative contribution lower than 0,5%	
A3: waste and particle emission	Less than 10 <sup>-5</sup> kg/kg of finished product	Sensitivity study demonstrates a relative contribution lower than 0,5%	

For the allocation procedure and principles, consider the following table:

Table 4: Allocation procedure and principles

Module	Allocation Principle
Al	All data are referred to 1 kg of product • Al: electricity is allocated to the whole plant production
A3	All data are referred to 1 kg of powder packaged product • A3-wastes: all data are allocated to the whole plant production





### 7. ENVIRONMENTAL PERFORMANCE & INTERPRETATION

### GWP<sub>100</sub>



#### AP

Acidification Potential refers to the emission of specific acidifying substances (i.e. NOx, SOx) in the air. These substances decrease the pH of the rainfall with predictable damages to the ecosystem.



Eutrophication Potential refers to the nutrient enrichment of flowing water, which determines unbalance in aquatic ecosystems and causes the death of the aquatic fauna.

#### ODP

EP



Ozone Depletion Potential refers to the degradation of the stratospheric layer of the ozone involved in blocking the UV component of sunrays. Depletion is due to particularly reactive components that originate from chlorofluorocarbon (CFC) or chlorofluoromethanes (CFM).

#### POCP



The Photochemical Ozone Creation Potential is the ozone formation in low atmosphere. This is quite common in the cities where a great amount of pollutants (like VOC and NOx) are emitted every day (industrial emissions and vehicles). It is mainly diffused during the summertime.



ADP<sub>e</sub> (elements)

Abiotic Depletion Potential elements refers to the depletion of the mineral resources.



#### **ADP**<sub>f</sub> (fossil fuel)

ΕΡŊ®

Abiotic Depletion Potential fossil fuel refers to the depletion of the fossil fuel resources.

The following tables show the environmental impacts for the products considered according to CML methodology (2001 - Jan.2016, ver. 4.7). All the results are referred to the declared unit (see § 4).

# Mapedeck Primer 200

Table 5: Mapedeck Primer 200: environmental categories referred to the declared unit			
Environm	nental category	Unit	A1-A3
	GWP <sub>100</sub>	(kg CO <sub>2</sub> eq.)	1,49E+00
	ADPe (element)	(kg Sb eq.)	7,71E-03
	ADPf (fossil)	(MJ)	3,70E+01
	AP	(kg SO <sub>2</sub> eq.)	1,28E-02
	EP	(kg (PO₄)³-eq.)	1,36E-03
	ODP	(kg R-11 eq.)	2,19E-07
	РОСР	(kg ethylene eq.)	8,38E-04
<b>GWP</b> <sub>100</sub> : Global Warmin <b>AP</b> : Acidification Poten <b>ADPf</b> : Abiotic Depletion	g Potential; <b>ADPe</b> : Abiotic Depletion tial; <b>POCP</b> : Photochemical Ozone C Potential (fossil)	n Potential (elements); <b>EP</b> : Creation Potential; <b>ODP</b> : O	Eutrophication Potential; zone Depletion Potential;

**EPD**®



Table 6: Mapedeck Primer 200: other environmental indicators referred to the declared unit		
Environmental Indicator	Unit	A1-A3
RPEE	MJ	1,93E+00
RPEM	MJ	-
TPE	MJ	1,93E+00
NRPE	МЈ	3,87E+01
NRPM	МЈ	-
TRPE	МЈ	3,87E+01
SM	kg	-
RSF	МЈ	-
NRSF	МЈ	-
W	m <sup>3</sup>	3,36E-02

Table 7: Mapedeck Primer 200: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			





# Mapedeck Flexiscreed

Table 8: Mapedeck Flexiscreed: environmental categories referred to the declared unit			
Environmental category Unit A1-A3			A1-A3
	GWP <sub>100</sub>	(kg CO2 eq.)	1,50E+00
	ADPe (element)	(kg Sb eq.)	1,10E+01
	ADPf (fossil)	(CM)	2,15E+01
	АР	(kg SO <sub>2</sub> eq.)	1,23E-02
	EP	(kg (PO₄)³·eq.)	5,60E-03
	ODP	(kg R-11 eq.)	8,96E-05
	РОСР	(kg ethylene eq.)	7,50E-01
GWP <sub>100</sub> : Global Warming Potential; ADPe: Abiotic Depletion Potential (elements); EP: Eutrophication Potential;			

ADPf: Abiotic Depletion Potential (fossil)

**Mapedeck Soft Design System** 





Table 9: Mapedeck Flexiscreed: other environmental indicators referred to the declared unit		
Unit	A1-A3	
MJ	3,11E+01	
MJ	-	
MJ	3,11E+01	
MJ	2,83E+01	
MJ	-	
МЈ	2,83E+01	
kg	-	
МЈ	-	
МЈ	-	
m <sup>3</sup>	1,08E+00	
	nvironmental indicators refer Unit MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ MJ	

Table 10: Mapedeck Flexiscreed: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



# Maperubber Black 25

Table 11: Maperubber Black 25: environmental categories referred to the declared unit			
Environmental category Unit A1-A3			A1-A3
	GWP <sub>100</sub>	(kg CO2 eq.)	2,69E+00
	ADPe (element)	(kg Sb eq.)	1,36E-05
	ADPf (fossil)	(LM)	7,67E+01
	АР	(kg SO <sub>2</sub> eq.)	1,09E-02
	EP	(kg (PO₄)³·eq.)	4,12E-03
	ODP	(kg R-11 eq.)	6,42E-07
	РОСР	(kg ethylene eq.)	1,31E-03
GWP <sub>100</sub> : Global Warming Potential; ADPe: Abiotic Depletion Potential (elements); EP: Eutrophication Potential; AP: Additional Potential: POCP: Detector			

ADPf: Abiotic Depletion Potential (fossil)

**Mapedeck Soft Design System** 







Table 12: Maperubber Black 25: other environmental indicators referred to the declared unit		
Environmental Indicator	Unit	A1-A3
RPEE	MJ	2,48E+00
RPEM	МЈ	-
TPE	МЈ	2,48E+00
NRPE	МЈ	8,46E+01
NRPM	МЈ	-
TRPE	МЈ	8,46E+01
SM	kg	-
RSF	МЈ	-
NRSF	МЈ	-
W	m <sup>3</sup>	6,63E+00

Table 13: Maperubber Black 25: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



# Mapedeck Soft Design

Table 14: Mapedeck Soft Design: environmental categories referred to the declared unit			
Environmental category		Unit	A1-A3
My s	GWP <sub>100</sub>	(kg CO <sub>2</sub> eq.)	2,24E+00
	ADPe (element)	(kg Sb eq.)	5,53E-06
	ADPf (fossil)	(MJ)	3,93E+01
	AP	(kg SO <sub>2</sub> eq.)	1,08E-02
	EP	(kg (PO₄)³-eq.)	4,05E-03
	ODP	(kg R-11 eq.)	4,21E-08
	РОСР	(kg ethylene eq.)	6,06E-04
<b>GWP</b> <sub>100</sub> : Global Warming Potential; <b>ADPe</b> : Abiotic Depletion Potential (elements); <b>EP</b> : Eutrophication Potential; <b>AP</b> : Acidification Potential: <b>POCP</b> : Photochemical Ozone Creation Potential: <b>ODP</b> : Ozone Depletion Potential:			

ADPf: Abiotic Depletion Potential (fossil)





Table 15: <b>Mapedeck Soft Design</b> : other environmental indicators referred to the declared unit			
Environmental Indicator	Unit	A1-A3	
RPEE	MJ	1,38E+01	
RPEM	MJ	-	
TPE	MJ	1,38E+01	
NRPE	МЈ	4,18E+01	
NRPM	МЈ	-	
TRPE	МЈ	4,18E+01	
SM	kg	-	
RSF	МЈ	-	
NRSF	МЈ	-	
W	m <sup>3</sup>	9,93E-01	

Table 16: Mapedeck Soft Design: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



# Maperubber EPDM 15

Table 17: Maperubber EPDM 15: environmental categories referred to the declared unit			
Environm	ental category	Unit	A1-A3
Myy	GWP <sub>100</sub>	(kg CO <sub>2</sub> eq.)	2,69E+00
	ADPe (element)	(kg Sb eq.)	1,36E-05
	ADPf (fossil)	(LM)	7,66E+01
	AP	(kg SO <sub>2</sub> eq.)	1,09E-02
	EP	(kg (PO₄)³·eq.)	4,12E-03
	ODP	(kg R-11 eq.)	6,42E-07
	РОСР	(kg ethylene eq.)	1,31E-03
GWP <sub>100</sub> : Global Warming Potential; ADPe: Abiotic Depletion Potential (elements); EP: Eutrophication Potential; AP: Acidification Potential: POCP: Photochemical Ozone Creation Potential: ODP: Ozone Depletion Potential			

ADPf: Abiotic Depletion Potential (fossil)

**Mapedeck Soft Design System** 







Table 18: Maperubber EPDM 15: other environmental indicators referred to the declared unit			
Environmental Indicator	Unit	A1-A3	
RPEE	MJ	2,48E+00	
RPEM	MJ	-	
TPE	MJ	2,48E+00	
NRPE	МЈ	8,46E+01	
NRPM	МЈ	-	
TRPE	МЈ	8,46E+01	
SM	kg	-	
RSF	МЈ	-	
NRSF	МЈ	-	
W	m <sup>3</sup>	6,63E+00	

Table 19: MMaperubber EPDM 15: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



# Mapedeck Finish 111 TSR

Table 20: Mapedeck Finish 111 TSR: environmental categories referred to the declared unit			
Environmental category Uni			A1-A3
Myy	GWP <sub>100</sub>	(kg CO <sub>2</sub> eq.)	2,71E+00
	ADPe (element)	(kg Sb eq.)	1,14E-02
	ADPf (fossil)	(MJ)	5,70E+01
	АР	(kg SO <sub>z</sub> eq.)	1,27E-02
	EP	(kg (PO₄)³-eq.)	3,02E-03
	ODP	(kg R-11 eq.)	3,10E-07
	РОСР	(kg ethylene eq.)	1,41E-03
<b>GWP</b> <sub>100</sub> : Global Warming Potential; <b>ADPe</b> : Abiotic Depletion Potential (elements); <b>EP</b> : Eutrophication Potential; <b>AP</b> : Acidification Potential: <b>POCP</b> : Photochemical Ozone Creation Potential: <b>ODP</b> : Ozone Depletion Potential:			

ADPf: Abiotic Depletion Potential (fossil)

**Mapedeck Soft Design System** 





Table 21: Mapedeck Finish 111 TSR: other environmental indicators referred to the declared unit			
Environmental Indicator	Unit	A1-A3	
RPEE	MJ	2,38E+00	
RPEM	MJ	-	
TPE	MJ	2,38E+00	
NRPE	МЈ	5,93E+01	
NRPM	МЈ	-	
TRPE	МЈ	5,93E+01	
SM	kg	-	
RSF	МЈ	-	
NRSF	МЈ	-	
W	m <sup>3</sup>	3,71E-02	

Table 22: **Mapedeck Finish 111 TSR**: waste production and other output flows referred to the declared unit

Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



# Mapedeck Wax

Table 23: Mapedeck Wax: environmental categories referred to the declared unit			
Environmental category		Unit	A1-A3
	GWP <sub>100</sub>	(kg CO2 eq.)	9,77E-01
	ADPe (element)	(kg Sb eq.)	4,79E-03
	ADPf (fossil)	(LM)	2,40E+01
	АР	(kg SO <sub>2</sub> eq.)	5,93E-03
	EP	(kg (PO₄)³·eq.)	1,44E-03
	ODP	(kg R-11 eq.)	2,05E-07
	РОСР	(kg ethylene eq.)	6,12E-04
<b>GWP</b> <sub>100</sub> : Global Warmin	g Potential; <b>ADPe</b> : Abiotic Depletion	n Potential (elements); <b>EP</b> :	Eutrophication Potential;

ADPf: Abiotic Depletion Potential (fossil)

**Mapedeck Soft Design System** 







Table 24: Mapedeck Wax: other environmental indicators referred to the declared unit			
Unit	A1-A3		
МЈ	8,48E-01		
МЈ	-		
МЈ	8,48E-01		
МЈ	2,52E+01		
МЈ	-		
МЈ	2,52E+01		
kg	-		
МЈ	-		
МЈ	-		
m <sup>3</sup>	1,29E-02		
	mental indicators referred to Unit MJ MJ MJ MJ MJ MJ MJ kg MJ MJ MJ MJ MJ MJ		

Table 25: Mapedeck Wax: waste production and other output flows referred to the declared unit			
Output flow	Unit	A1-A3	
NHW	kg	5,25E-03	
HW	kg	4,21E-06	
RW	kg	0,00E+00	
Components for re-use	kg	-	
Materials for recycling	kg	-	
Materials for energy recovery	kg	-	
Exported energy	МЈ	-	
HW Hazardous waste disposed; NHW Non Hazardous waste disposed; RW Radioactive waste disposed			



Tables above and following plots show absolute results and relative contribution for the environmental categories considered in this EPD.

The module **A1** (raw materials extraction and processing) has the greatest contribution for all the environmental categories included in this study. Considering ODP and ADPe, module **A1** highlights a relative contribution close to 100%.

The electricity consumption used for the manufacturing process doesn't affect significantly the results.

The module A2 (raw materials transportation) gives a negative contribution to POCP due to the NO and NO<sub>2</sub> emission factors (for more details, see the methodology used: *HBEFA* -*Handbook Emission Factors for Road Transport*).











Table 27: Environmental Impact of Mapedeck Litescreed as percentage referred to the declared unit





**EPD**<sup>®</sup>





Table 30: Environmental Impact of Mapedeck Wax as percentage referred to the declared unit



23 



The following plot and table show the comparison between  ${\rm GWP}_{\rm 100}$  and the consumption of single component for the system studied.



More details about electrical mix used in this EPD (Italian grid mix – 2014), is shown below:

	Data source	Amount	Unit
Electricity grid mix (IT) – 2014	GaBi database	0,4020	kg CO <sub>2</sub> -eqv/kWh
Electricity from photovoltaic (IT) – 2014	GaBi database	0,0641	kg CO <sub>2</sub> -eqv/kWh



# 8. DATA QUALITY

Table 29: Data quality				
Dataset & Geographical reference	Database (source)	Temporary reference		
A1; A3				
Polymer Dispersions (EU)	EcoProfile EPDLA	2015		
Fillers (EU)	GaBi Database	2017		
Additives (EU)	GaBi Database; EFCA EPD IBU 20150091; PlasticEurope	2005 – 2017		
Electricity grid mix (IT)	GaBi Database	2014		
Electricity from photovoltaic (IT)	GaBi Database	2014		
Packaging components (EU)	GaBi Database, PlasticEurope	2005 – 2017		
A2; A4				
Truck transport (euro 3, 27t payload – GLO)	GaBi Database	2017		
Light Train (Gross Ton Weight 500t - GLO)	GaBi Database	2017		
Oceanic ship (27500 DWT - GLO)	GaBi Database	2017		
Electricity grid mix (EU)	GaBi Database	2014		
Diesel for transport (EU)	GaBi Database	2014		
Heavy Fuel Oil (EU)	GaBi Database	2014		

All data included in table above refer to a period between 2005 and 2017; the most relevant ones are specific from supplier, while the others (i.e. transport and minor contribution dataset), come from European and global databases.

All dataset are not more than 10 years old according to EN 15804 § 6.3.7 "Data quality requirements". The only exception is represented by raw materials coming from PlasticEurope database.

Primary data concern the year 2017 and represent the whole annual production.





# 9. VERIFICATION AND REGISTRATION

EPD of construction products may not be comparable if they do not comply with EN 15804.

Environmental product declarations within the same product category from different programs may not be comparable.

PCR:	PCR 2012:01 Construction products and Construction services, Version 2.2, 2017-05-30
PCR review was conducted by:	The Technical Committee of the International EPD® System. Chair: Massimo Marino Contact via <b>info@environdec.com</b>
Independent verification of the declaration and data, according to ISO 14025	<ul> <li>EPD Process Certification (Internal)</li> <li>EPD Verification (external)</li> </ul>
Third party verifier:	Certiquality S.r.l. Number of accreditation: 003H rev14
Accredited or approved by:	Accredia
Procedure for follow-up of data during EPD validity involves third-party verifier	⊠ Yes □ No

### CEN standard EN15804 served as the core PCR

### **10.REFERENCES**

- EN 15804:2014 SUSTAINABILITY OF CONSTRUCTION WORKS -ENVIRONMENTAL PRODUCT DECLARATIONS - CORE RULES FOR THE PRODUCT CATEGORY OF CONSTRUCTION PRODUCTS
- GENERAL PROGRAMME INSTRUCTIONS OF THE INTERNATIONAL EPD®
   SYSTEM. VERSION 3.0
- HBEFA: HANDBOOK EMISSION FACTORS FOR ROAD TRANSPORT
- ISO 14025 ENVIRONMENTAL LABELS AND DECLARATIONS TYPE III ENVIRONMENTAL DECLARATIONS - PRINCIPLES AND PROCEDURES
- ISO 14044 ENVIRONMENTAL MANAGEMENT LIFE CYCLE ASSESSMENT – REQUIREMENTS AND GUIDELINES
- MARINE EQUIPMENT DIRECTIVE (MED) 96/98/EC

 PCR 2012:01; "PRODUCT GROUP CLASSIFICATION: MULTIPLE UN CPC CODES CONSTRUCTION PRODUCTS AND CONSTRUCTION SERVICES"; VERSION 2.2



## **CONTACT INFORMATION**

EPD owner:	ADHESIVES - SEALANTS - CHEMICAL PRODUCTS FOR BUILDING Mapei SpA www.mapei.it
LCA author:	ADHESTVES - SEALANTS - CHEMICAL PRODUCTS FOR BUILDING Mapei SpA www.mapei.it; Environmental Sustainability Office
Programme operator:	EPD International AB info@environdec.com





SEDE MAPEI SpA Via Cafiero, 22 - 20158 Milano Tel. +39-02-37673.1 Fax +39-02-37673.214 Internet: www.mapei.com E-mail: mapei@mapei.it



