

WOVEN, KNITTED OR CROCHETED FABRICS (OF SYNTHETIC FIBRES)

PRODUCT CATEGORY CLASSIFICATION: UN CPC 267, 281

2012:14 VERSION 2.13



TABLE OF CONTENTS

2 General information	7
2.2 Scope of PCR 3 PCR review and background information	² 7
2.2 Scope of PCR 3 PCR review and background information	² 7
PCR review and background information	7
3.1 PCR review	7
3.3 Existing PCRs for the product category	
3.4 Reasoning for development of PCR	
3.5 Underlying studies	
4 Goal and scope, life cycle inventory and life cycle impact assessment	8
4.1 Functional unit	
4.2 Reference service life (RSL)	
4.3 System boundary	
4.4 System diagram	11
4.5 Cut-off rules	11
4.6 Allocation rules	12
4.7 Data quality requirements	12
4.8 Impact categories and impact assessment	13
4.9 Other calculation rules and scenarios	13
5 Content and format of EPD	16
5.1 EPD languages	16
5.2 Units and quantities	16
5.3 Use of images in EPD	17
5.4 EPD reporting format	17
6 Glossary	26
7 References	27
8 Version history of PCR	٥,



1 INTRODUCTION

This document constitutes Product Category Rules (PCR) developed in the framework of the International EPD® System: a programme for type III environmental declarations¹ according to ISO 14025:2006. Environmental Product Declarations (EPD) are voluntary documents for a company or organisation to present transparent information about the life cycle environmental impact for their goods or services.

The rules for the overall administration and operation of the programme are the General Programme Instructions, publicly available at www.environdec.com. A PCR complements the General Programme Instructions and the standards by providing specific rules, requirements and guidelines for developing an EPD for one or more specific product categories (see Figure 1). A PCR should enable different practitioners using the PCR to generate consistent results when assessing products of the same product category.




Figure 1 Illustration PCR in relation to the hierarchy of standards and other documents.

Within the present PCR, the following terminology is adopted:

- The term "shall" is used to indicate what is obligatory.
- The term "should" is used to indicate a recommendation, rather than a requirement.
- The term "may" or "can" is used to indicate an option that is permissible

For the definition of terms used in the document, see the normative standards.

A PCR is valid for a pre-determined period of time to ensure that it is updated at regular intervals. The latest version of the PCR is available via www.environdec.com. Stakeholder feedback on PCRs is very much encouraged. Any comments on this PCR document may be given via the PCR Forum at www.environdec.com or sent directly to the PCR moderator during its development or during the period of validity.

Any references to this document should include the PCR registration number, name and version.

The programme operator maintains the copyright of the document to ensure that it is possible to publish, update when necessary, and available to all organisations to develop and register EPDs. Stakeholders participating in PCR development should be acknowledged in the final document and on the website.

-

¹ Type III environmental declarations in the International EPD® System are referred to as EPD, Environmental Product Declarations.



2 GENERAL INFORMATION

2.1 ADMINISTRATIVE INFORMATION

Name:	Woven, knitted or crocheted fabrics (of synthetic fibres)
Registration number and version:	2012:14, version 2.13
Programme:	EPD ®
	The International EPD® System
Programme operator:	EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden.
	Website: www.environdec.com E-mail: info@environdec.com
PCR moderator:	Stefania Dal Corso stefania.dalcorso@centrocot.it
PCR Committee:	Eurojersey Spa & Centro Tessile Cotoniero e Abbigliamento Spa
Date of publication and last revision:	2020-11-18 (Version 2.13)
	Version 1.0 was published 2012-12-07. A version history is available in Section 8.
Valid until:	2021-09-23
Schedule for renewal:	A PCR is valid for a pre-determined period of time to ensure that it is updated at regular intervals. When the PCR is about to expire the PCR moderator shall initiate a discussion with the Secretariat how to proceed with updating the document and renewing its validity.
	A PCR document may be revised during its period of validity provided significant and well-justified proposals for changes or amendments are presented. See www.environdec.com for up-to-date information and the latest version.
Standards conformance:	 General Programme Instructions of the International EPD[®] System, version 3.0, based on ISO 14025 and ISO 14040/14044
	 PCR Basic Module, CPC Division 26 Yarn and thread, woven and tufted textile fabrics, version 3.01, dated 2018-11-06
	 PCR Basic Module, CPC Division 28 Knitted or crocheted fabrics, wearing apparel, version 3.01, dated 2018-11-06
PCR language(s):	This PCR was developed and is available in English. In case of translated versions the English version takes precedence in case of any discrepancies.

2.2 SCOPE OF PCR

2.2.1 PRODUCT CATEGORY DEFINITION AND DESCRIPTION

This document provides Product Category Rules (PCR) for the assessment of the environmental performance of Woven, knitted or crocheted fabrics and the declaration of this performance by an EPD. The product category corresponds to UN CPC 267 and 281.



This PCR is intended to cover all woven or knitted synthetic fibres, intended for application in several sectors as apparel. <u>Synthetic</u> fibres are derived from chemical processes. Synthetic fibres are:

- Acrylic
- Modacrylic
- Polyamide (nylon)
- Polyethylene
- Polyester
- Polypropylene
- Polyvinyl Chloride
- Polyurethane (elastan)
- Aramids (Kevlar, Nomex and Twaron)
- Elastodiene
- Metalized fibre

In particular the UN CPC classification is:

Group	Class	Description
267		Woven fabrics (except special fabrics) of man-made filaments and staple fibres
	2671	Woven fabrics of man-made filament yarn, obtained from high tenacity yarn of nylon or other polyamides, of polyesters or of viscose rayon: woven fabrics of synthetic filaments yarn, obtained from strip or the like; woven fabrics of synthetic filament yarn, consisting of layers of parallel yarns superimposed on each other at angles, the layers being bonded at the intersections of the yarns (including mesh scrims)
	2672	Other woven fabrics of man-made filament yarn, containing 85% or more by weight of such filaments
	2673	Other woven fabrics of man-made filament yarn,
	2674	Woven fabrics of synthetic staple fibres, containing 85% or more by weight of synthetic staple fibres.
	2675	Woven fabrics of artificial staple fibres, containing 85% or more by weight of artificial staple fibres.
	2676	Woven fabrics of man-made staple fibres, containing less than 85% of such fibres, mixed mainly or solely with cotton.
	2677	Woven fabrics of man-made staple fibres, containing less than 85% of such fibres, mixed mainly or solely with wool or fine animal hair.
	2679	Other woven fabrics of man-made staple fibres.
281		Knitted or crocheted fabrics
	2811	Pile fabrics and terry fabrics, knitted or crocheted
	2819	Other knitted or crocheted fabrics



For additional information, see http://unstats.un.org/unsd/cr/registry/regcst.asp?Cl=25.

2.2.2 GEOGRAPHICAL REGION

This PCR is applicable to be used globally.

2.2.3 EPD VALIDITY

An EPD based on this PCR shall be valid from its registration and publication at www.environdec.com and for a five year period starting from the date of the verification report ("approval date"), or until the EPD has been de-registered from the International EPD® System.

An EPD shall be updated and re-verified during its validity if changes in technology or other circumstances have led to:

- an increase of 10% or more of any of the indicators listed in Section 5.4.5.1,
- errors in the declared information, or
- significant changes to the declared product information, content declaration, or additional environmental information.

If such changes have occurred, but the EPD is not updated, the EPD owner shall contact the Secretariat to de-register the EPD.



3 PCR REVIEW AND BACKGROUND INFORMATION

This PCR was developed in accordance with the process described in the General Programme Instructions of the International EPD[®] System, including PCR review and open consultation.

3.1 PCR REVIEW

3.1.1 VERSION 2.0

PCR review panel:	The Technical Committee of the International EPD® System. A full list of members available on www.environdec.com . The review panel may be contacted via info@environdec.com .
	Members of the Technical Committee were requested to state any potential conflict of interest with the PCR moderator or PCR committee, and were excused from the review.
Chair of the PCR review:	Lars-Gunnar Lindfors
Review dates:	2015-11-04 until 2015-12-15

3.2 OPEN CONSULTATION

3.2.1 VERSION 1.0

This PCR was available for open consultation from 2012-10-24 until 2012-11-23, during which any stakeholder was able to provide comments by posting on the PCR forum on www.environdec.com or by contacting the PCR moderator.

Stakeholders were invited via e-mail or other means to take part in the open consultation, and were encouraged to forward the invitation to other relevant stakeholders.

3.2.2 VERSION 2.0

This PCR was available for open consultation from 2015-02-27 until 2015-04-27, during which any stakeholder was able to provide comments by posting on the PCR forum on www.environdec.com or by contacting the PCR moderator.

Stakeholders were invited via e-mail or other means to take part in the open consultation, and were encouraged to forward the invitation to other relevant stakeholders.

3.3 EXISTING PCRS FOR THE PRODUCT CATEGORY

As part of the development of this PCR, existing PCRs were considered in order to avoid overlaps in scope. The existence of such documents was checked in the public PCR listings of the following programmes based on ISO 14025 or similar:

International EPD® System. www.environdec.com.

Further information will be added in a future revision of this PCR.

3.4 REASONING FOR DEVELOPMENT OF PCR

This PCR was developed in order to enable publication of Environmental Product Declarations (EPD) for this product category based on ISO 14025, ISO 14040/14044 and other relevant standards to be used in different applications and target audiences.

3.5 UNDERLYING STUDIES

Further information will be added in a future revision of this PCR.



4 GOAL AND SCOPE, LIFE CYCLE INVENTORY AND LIFE CYCLE IMPACT ASSESSMENT

The goal of this section is to provide specific rules, requirements and guidelines for developing an EPD for the product category as defined in Section 2.2.1.

4.1 FUNCTIONAL UNIT

The functional unit is defined as 1 (one) square meter of fabric.

The functional unit shall be declared in the EPD®. The environmental impact shall be given per functional unit. A description of the function of the product should be included in the EPD®, if relevant.

4.2 REFERENCE SERVICE LIFE (RSL)

Not applicable for this product category.

4.3 SYSTEM BOUNDARY

The International EPD® System uses an approach where all attributional processes from "cradle to grave" should be included using the principle of "limited loss of information at the final product". This is especially important in the case of business-to-consumer communication

The scope of this PCR and EPDs based on it is cradle-to-grave.

4.3.1 LIFE CYCLE STAGES

For the purpose of different data quality rules and for the presentation of results, the life cycle of products is divided into three different life cycle stages:

- Upstream processes (from cradle-to-gate);
- Core processes (from gate-to-gate)
- Downstream processes (from gate-to-grave)

In the EPD, the environmental performance associated with each of the three life-cycle stages above shall be reported separately. The processes included in the scope of the PCR and belonging to each life cycle stage are described in Sections 4.3.1.1–4.3.1.3.

4.3.1.1. Upstream processes

The following attributional processes are part of the product system and classified as upstream processes:

- Extraction or synthesis of the raw materials (e.g. caprolactame, polyol, MDI, ...);
- Production of materials (synthetic fibres);
- Production of ancillaries used in the up-stream and core processes;
- Production of pigments and dyes used in the up-stream and core processes;
- Production of packaging, if relevant;
- End of life treatment of waste, if relevant;
- Waste water treatment, if relevant.

Raw Materials entering the system shall be split into:

- Virgin raw materials
- Recycled raw materials



The following processes shall NOT be explicitly included:

- Transportation of raw materials;
- Building of the production site or other infrastructures (capital equipment);
- Personnel activities as well as the contribution of travel to work.
- Scraps coming from demolition of building or other infrastructures.

Upstream processes not listed may also be included. All elementary flows at resource extraction shall be included, except for the flows that fall under the general cut-off rule in Section 4.5.

4.3.1.2. Core processes

The following attributional processes are part of the product system and classified as core processes:

- Manufacturing of the finished product (woven or knitted synthetic fibres);
- Transportation of materials, ancillaries, pigments and dyes to the core;
- Internal transportation of fabric to stockroom or warehouse;
- End of life treatment of waste, if relevant
- Waste water treatment, if relevant

The following processes shall NOT be explicitly included:

- Building of the production site or other infrastructures (capital equipment);
- Personnel activities as well as the contribution of travel to work.
- Scraps coming from demolition of building or other infrastructures.
- Travel to and from work by personnel.
- Research and development activities.

The quality control, packaging, garment manufacturing phases are NOT taken into consideration due to the low environmental impact that it produces.

Manufacturing processes not listed may also be included. The production of the raw materials used for production of all product parts shall be included. A minimum of 99% of the total weight of the declared product including packaging shall be included.

4.3.1.3. Downstream processes

The following attributional processes are part of the product system and classified as downstream processes:

Transportation of the products to the retailer/ consumers (considering an average market for the considered period; distances can be calculated to specific destinations or to a country or region/state/provincial capital).

It is voluntary to include:

- The use phase (use of the fabric: manufacturing of the final product); its impact depends on the type of garment made from the synthetic fabric;
- The consumer use of the product; the EDP may contain information about the environmental impact related to the usage phase: washing, drying, ironing;
- Recycling or handling of packaging waste/materials after use;
- Products end of life.

The voluntary phases should be accounted for separately.



4.3.2 OTHER BOUNDARY SETTING

4.3.2.1. Boundary towards nature

Boundaries to nature are defined as flows of material and energy resources from nature into the system. Emissions to air, water and soil cross the system boundary when they are emitted from or leaving the product system.

4.3.2.2. Boundaries in the life cycle

See Section 4.3.1. The EPD may present the information divided into additional sub-divisions.

4.3.2.3. Boundaries towards other technical systems

See Section 4.6.2.

4.3.2.4. Boundaries in time

The data shall be representative for the year/time frame for which the EPD is valid.

4.3.2.5. Boundaries in towards geography

The data for the core module shall be representative for the site/region where the respective process is taking place



4.4 SYSTEM DIAGRAM




Figure 2 System diagram illustrating the processes that are included in the product system, divided into upstream, core and downstream processes. It should be indicated if any omissions of life cycle stages are made in order to make the EPD® cover the full cradle-to-grave perspective.

4.5 CUT-OFF RULES

Data for elementary flows to and from the product system contributing to a minimum of 99% of the declared environmental impacts shall be included (not including processes that are explicitly outside the system boundary as described in Section 4.3).

The check for cut-off rules in a satisfactory way is through the combination of expert judgment based on experience of similar product systems and a sensitivity analysis in which it is possible to understand how the un-investigated input or output could affect the final results.



4.6 ALLOCATION RULES

4.6.1 CO-PRODUCT ALLOCATION

The following step-wise procedure shall be applied for multifunctional products and multiproduct processes:

- Allocation shall be avoided, if possible, by dividing the unit process into two or more sub-processes and collecting the
 environmental data related to these sub-processes.
- 2. If allocation cannot be avoided, the inputs and outputs of the system shall be partitioned between its different products or functions in a way that reflects the underlying physical relationships between them; i.e. they should reflect the way in which the inputs and outputs are changed by quantitative changes in the products or functions delivered by the system. Ancillary activities (e.g. office or plant heating, lighting, etc.) shall be allocated to the overall service production. Environmental burden shall be allocated to the whole production on the basis of the actual production. Economic allocation shall not be used because of its sensitivity to market specific conditions. Any other allocation procedures based on physical or chemical characteristics must be specified in the EPD.

4.6.2 REUSE, RECYCLING, AND RECOVERY

In the framework of the International EPD® System, the methodological choices for allocation for reuse, recycling and recovery have been set according to the polluter pays principle (PPP). This means that the generator of the waste shall carry the full environmental impact until the point in the product's life cycle at which the waste is transported to a scrapyard or the gate of a waste processing plant (collection site). The subsequent user of the waste shall carry the environmental impact from the processing and refinement of the waste but not the environmental impact caused in the "earlier" life cycles. See General Programme Instruction for further information and examples.

4.7 DATA QUALITY REQUIREMENTS

An LCA calculation requires two different kinds of information:

- data related to the environmental aspects of the considered system (such materials or energy flows that enter the production system). These data usually come from the company that is performing the LCA calculation.
- data related to the life cycle impacts of the material or energy flows that enter the production system. These data usually
 come from databases.

Data on environmental aspects shall be as specific as possible and shall be representative of the studied process.

Data on the life cycle of materials or energy inputs are classified into three categories – specific data, selected generic data, and proxy data, defined as follows:

- specific data (also referred to as "primary data" or "site-specific data") data gathered from the actual manufacturing plant where product-specific processes are carried out, and data from other parts of the life cycle traced to the specific product system under study, e.g. materials or electricity provided by a contracted supplier that is able to provide data for the actual delivered services, transportation that takes place based on actual fuel consumption, and related emissions, etc.,
- generic data (sometimes referred to as "secondary data"), divided into:
 - **selected generic data** data from commonly available data sources (e.g. commercial databases and free databases) that fulfil prescribed data quality characteristics for precision, completeness, and,
 - proxy data data from commonly available data sources (e.g. commercial databases and free databases) that do not fulfil all of the data quality characteristics of "selected generic data".

As a general rule, specific data shall always be used, if available, after performing a data quality assessment. It is mandatory to use specific data for the core processes as defined above. For the upstream processes, downstream processes, and infrastructure, generic data may also be used if specific data are not available.

Any data used should preferably represent average values for a specific reference year. However, the way these data are generated could vary, e.g. over time, and in such cases they should have the form of a representative annual average value for a specified reference period. Such deviations should be declared.



4.7.1 RULES FOR USING GENERIC DATA

The attributional LCA approach in the International EPD® System forms the basic prerequisites for selecting generic data. To allow the classification of generic data as "selected generic data", they shall fulfil selected prescribed characteristics for precision, completeness, and representativeness (temporal, geographical, and technological), such as:

- the reference year must be as current as possible and preferably assessed to be representative for at least the validity period
 of the EPD,
- the cut-off criteria to be met on the level of the modelled product system are the qualitative coverage of at least 99% of energy, mass, and overall environmental relevance of the flows,
- completeness in which the inventory data set should, in principle, cover all elementary flows that contribute to a relevant degree
 of the impact categories, and
- the representativeness of the resulting inventory in the given temporal, technological, and geographical reference should, as a
 general principle, be better than ±5% of the environmental impact of fully representative data.

If selected generic data that meets the requirements of the International EPD® System are not available as the necessary input data, proxy data may be used and documented. The environmental impacts associated with proxy data shall not exceed 10% of the overall environmental impact from the product system.

The EPD may include a data quality declaration to demonstrate the share of specific data, selected generic data and proxy data for the environmental impacts.

4.8 IMPACT CATEGORIES AND IMPACT ASSESSMENT

The EPD shall declare the default impact categories as described in the General Programme Instructions. The characterisation models and factors to use for the default impact categories are available on www.environdec.com and shall be updated on a regular basis based on the latest developments in LCA methodology and ensuring the market stability of EPDs. The source and version of the characterisation models and the factors used shall be reported in the EPD. Alternative regional life cycle impact assessment methods and characterisation factors are allowed to be calculated and displayed in addition to the default list. If so, the EPD shall contain an explanation of the difference between the different sets of indicators, as they may appear to the reader to display duplicate information.

4.9 OTHER CALCULATION RULES AND SCENARIOS

4.9.1 UPSTREAM PROCESSES

The following requirements apply to the upstream processes:

- Data referring to processes and activities upstream in a supply chain over which an organisation has direct management control shall be specific and collected on site.
- Data referring to contractors that supply main parts, packaging, or main auxiliaries should be requested from the contractor as specific data, as well as infrastructure, where relevant.
- The transport of main parts and components along the supply chain to a distribution point (e.g. a stockroom or warehouse) where the final delivery to the manufacturer can take place based on the actual transportation mode, distance from the supplier, and vehicle load.
- In case specific data is lacking, selected generic data may be used. If this is also lacking, proxy data may be used.
- For the electricity used in the upstream processes, electricity production impacts shall be accounted for in this priority when specific data are used in the upstream processes:



- Specific electricity mix as generated, or purchased, from an electricity supplier, demonstrated by a Guarantee of Origin (or similar, where reliability, traceability, and the avoidance of double-counting are ensured) as provided by the electricity supplier. If no specific mix is purchased, the residual electricity mix from the electricity supplier shall be used.²
- 2. National residual electricity mix or residual electricity mix on the market
- 3. National electricity production mix or electricity mix on the market.

The mix of electricity used in upstream processes shall be documented in the EPD, where relevant.

Packaging: specific data shall be used for the consumer packaging production if it is under the direct control of the organization or if the environmental impact related to the consumer packaging production is more than 10% of the total product environmental indicators. In other cases, generic data may be used. When consumer packaging shows the organization's logo, the LCA report should report the exerted/non exerted direct control on the production of consumer packaging by the organization.

4.9.2 CORE PROCESSES

The following requirements apply to the core processes:

- Specific data shall be used for the assembly of the product and for the manufacture of main parts as well as for on-site generation of steam, heat, electricity, etc., where relevant.
- For the electricity used in the core processes, electricity production impacts shall be accounted for in this priority:
 - Specific electricity mix as generated, or purchased, from an electricity supplier, demonstrated by a Guarantee of Origin (or similar, where reliability, traceability, and the avoidance of double-counting are ensured) as provided by the electricity supplier. If no specific mix is purchased, the residual electricity mix from the electricity supplier shall be used.³
 - 2. National residual electricity mix or residual electricity mix on the market
 - 3. National electricity production mix or electricity mix on the market.

The mix of electricity used in the core processes shall be documented in the EPD, where relevant.

- Transport from the final delivery point of raw materials, chemicals, main parts, and components (see above regarding upstream processes) to the manufacturing plant/place of service provision should be based on the actual transportation mode, distance from the supplier, and vehicle load, if available.
- Waste treatment processes of manufacturing waste should be based on specific data, if available.
- Data shall be verifiable by providing technical documentation. If these data sources do not supply the necessary data, other generic data sources, such as those listed at the http://lct.jrc.ec.europa.eu, may be used. It is recommended to consistently use one database for the entire LCA.

4.9.3 DOWNSTREAM PROCESSES

The following requirements apply to the downstream processes:

- Data for the use stage are usually based on scenarios, but specific data should be used when available and relevant.
- Data on the pollutant emissions from the use stage should be based on documented tests, verified studies in conjunction with average or typical product use, or recommendations concerning suitable product use. Whenever applicable, test methods shall be internationally recognised.
- The use of electricity in the region/country where the product is used (as specified in the geographical scope of the EPD) shall be accounted for in the following priority:
 - 1. National residual electricity mix or residual mix on the market

² The residual electricity mix is the mix when all contract-specific electricity that has been sold to other customers has been subtracted from the total production mix of the electricity supplier.

³ The residual electricity mix is the mix when all contract-specific electricity that has been sold to other customers has been subtracted from the total production mix of the electricity supplier.



2. National electricity production mix or electricity mix on the market

The mix of electricity used in the downstream processes shall be documented in the EPD, where relevant.

- The transport of the product to the customer shall be described in the reference PCR, which should reflect the actual situation to the best extent possible. The following priority should be used:
 - 1. Actual transportation distances and types.
 - 2. Calculated as the average distance of a product of that product type transported by different means of transport modes.
 - 3. Calculated as a fixed long transport, such as 1 000 km transport by lorry or 10 000 km by airplane, according to product type.
- Scenarios for the end-of-life stage shall be technically and economically practicable and compliant with current regulations in
 the relevant geographical region based on the geographical scope of the EPD. Key assumptions regarding the end-of-life stage
 scenario shall be documented.



5 CONTENT AND FORMAT OF EPD

EPDs based on this PCR shall contain the information described in this section. Flexibility is allowed in the formatting and layout provided that the EPD still includes the prescribed information. A generic template for EPDs is available via www.environdec.com

As a general rule the EPD content:

- shall be in line with the requirements and guidelines in ISO 14020 (Environmental labels and declarations General principles),
- shall be verifiable, accurate, relevant and not misleading, and
- shall not include rating, judgements or direct comparison with other products.

An EPD should be made with a reasonable number of pages for the intended audience and use.

5.1 EPD LANGUAGES

EPDs should be published in English, but may also be published in additional languages. If the EPD is not available in English, it shall contain an executive summary in English including the main content of the EPD. This summary is part of the EPD and thus subject to the same verification procedure.

5.2 UNITS AND QUANTITIES

The following requirements apply for units and quantities:

- The International System of Units (SI units) shall be used, e.g., kilograms (kg), Joules (J) and metres (m). Reasonable multiples of SI units may be decided in the PCR to improve readability, e.g., grams (g) or megajoules (MJ). The following exceptions apply:
 - Resources used for energy input (primary energy) should be expressed as kilowatt-hours (kWh) or megajoules (MJ), including renewable energy sources, e.g., hydropower, wind power and geothermal power.
 - Water use should be expressed in cubic metres (m³)
 - Temperature should be expressed in degrees Celsius (°C),
 - Time should be expressed in the units most practical, e.g., seconds, minutes, hours, days or years.
- Three significant figures⁴ should be adopted for all results, The number of significant digits shall be appropriate and consistent.
- The thousand separator and decimal mark in the EPD shall follow one of the following styles (a number with six significant figures shown for illustration):
 - SI style (French version): 1 234,56
 - SI style (English version): 1 234.56

In case of potential confusion or intended use of the EPD in markets where different symbols are used, the EPD shall state what symbols are used for thousand separator and decimal mark.

- Dates and times presented in the EPD should follow the format in ISO 8601. For years, the prescribed format is YYYY-MM-DD, e.g., 2017-03-26 for March 26th, 2017.
- The result tables shall:
 - Only contain values or the letters "INA" (Indicator Not Assessed). It is not possible to specify INA for mandatory indicators. INA shall only be used for voluntary parameters that are not quantified because no data is available.⁵
 - Contain no blank cells, hyphens, less than or greater than signs or letters (except "INA").

© EPD INTERNATIONAL AB 2020. ALL USE IS SUBJECT TO OUR GENERAL TERMS OF USE PUBLISHED AT WWW.ENVIRONDEC.COM

⁴ Significant figures are those digits that carry meaning contributing to its precision. For example with two significant digits, the result of 123.45 shall be displayed as 120, and 0.12345 shall be displayed as 0.12. In scientific notation, these two examples would be displayed as 1.2*10² and 1.2*10².

⁵ This requirement does not intend to give guidance on what indicators are mandated ("shall") or voluntary.



- Use the value 0 only for parameters that have been calculated to be zero.
- Footnotes shall be used to explain any limitation to the result value.

5.3 USE OF IMAGES IN EPD

Images used in the EPD, especially pictures featured on the cover page, may in themselves be interpreted as an environmental claim. Images such as trees, mountains, wildlife that are not related to the declared product should therefore be used with caution and in compliance with national legislation and best available practices in the markets in which the EPD is intended to be used.

5.4 EPD REPORTING FORMAT

The reporting format of the EPD shall include the following sections:

- Cover page (see Section 5.4.1)
- Programme information (see Section 5.4.2)
- Product information (see Section 5.4.3)
- Content declaration (see Section 5.4.4)
- Environmental performance (see Section 5.4.5)
- References (see Section 5.4.8)

The following information shall be included, when applicable:

- Information related to Sector EPDs (see Section 5.4.6)
- Differences versus previous versions (see Section 5.4.7)
- Executive summary in English (see Section 5.4.9)

5.4.1 COVER PAGE

The cover page shall include:

- Product name and image,
- Name and logotype of EPD owner,
- The text "Environmental Product Declaration" and/or "EPD"
- Programme: The International EPD® System, <u>www.environdec.com</u>,
- Programme operator: EPD International AB
- Logotype of the International EPD® System,
- EPD registration number as issued by the programme operator⁶,
- Date of publication (issue): 20XX-YY-ZZ,
- Date of revision: 20XX-YY-ZZ, when applicable,
- Date of validity; 20XX-YY-ZZ
- A note that "An EPD should provide current information, and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com."
- A statement of conformity with ISO 14025,

⁶ The EPD shall not include a "registration number" if such is provided by the certification body, as this may be confused with the registration number issued by the programme operator.



5.4.2 PROGRAMME INFORMATION

The programme information section of the EPD shall include:

- Address of programme operator: EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden, E-mail: info@environdec.com
- The following mandatory statement from ISO 14025: "EPDs within the same product category but from different programmes may not be comparable."
- A statement that the EPD owner has the sole ownership, liability and responsibility of the EPD
- Information about verification⁷ and reference PCR in a table with the following format and contents:

Product category rules (PCR): 2012:14 Woven, knitted or crocheted fabrics. Version 2.1. UN CPC 267, 281.
PCR review was conducted by: The Technical Committee of the International EPD® System. Revuew chair: Lars-Gunnar Lindfors Contact via info@environdec.com
Independent third-party verification of the declaration and data, according to ISO 14025:2006:
☐ EPD process certification ☐ EPD verification
Third party verifier: <name, and="" of="" organisation="" party="" signature="" the="" third="" verifier=""></name,>
In case of certification bodies: Accredited by: <name accreditation="" and="" applicable="" body="" if="" number,="" of="" the="">.</name>
In case of individual verifiers: Approved by: The International EPD® System Technical Committee, supported by the Secretariat
Procedure for follow-up of data during EPD validity involves third party verifier:
□ Yes □ No

5.4.3 PRODUCT INFORMATION

The product information section of the EPD shall include:

- Address and contact information to EPD owner,
- Description of the organisation. This may include information on products- or management system-related certifications (e.g. ISO 14024 Type I environmental labels, ISO 9001- and 14001-certificates and EMAS-registrations) and other relevant work the organisation wants to communicate (e.g. SA 8000, supply-chain management and social responsibility),
- Name and location of production site,
- Product identification by name, and an unambiguous identification of the product by standards, concessions or other means,
- Identification of the product according to the UN CPC scheme system. Other relevant codes for product classification may also be included, e.g.
 - Common Procurement Vocabulary (CPV),
 - United Nations Standard Products and Services Code® (UNSPSC),
 - Classification of Products by Activity (NACE/CPA) or
 - Australian and New Zealand Standard Industrial Classification (ANZSIC),

⁷ If the EPD has been verified by an approved individual verifier who has received contractual assistance from a certification body that is not accredited, this certification body shall not be included in this table.



- Description of the product, its application/intended use and technical functions, e.g. expected service life time,
- Geographical scope of the EPD, i.e., for which geographical location(s) of use and end-of-life the product's performance has been calculated,
- Functional unit or declared unit,
- Reference service life (RSL), if applicable,
- Declaration of the year(s) covered by the data used for the LCA calculation and other relevant reference years,
- Reference to the main database(s) for generic data and LCA software used, if relevant,
- System diagram of the processes included in the LCA, divided into the life cycle stages,
- Description if the EPD system boundary is "cradle-to-gate", "cradle-to-gate with options" or "cradle-to-grave",
- Information on which life cycle stages are not considered (if any), with a justification of the omission,
- Relevant websites for more information or explanatory materials.
- the technical and functional characteristics of the fabric measured in accordance with the tests listed in Table 1 (Recognised standards should be use when referring to specific technical issues).
- product certification, if any

Characteristics	Reference standard L		
Constructive characteristics			
Composition	Reg UE n°1007/2011	%	
	Woven fabrics ISO 3572:1976	-	
	Knitted fabrics ISO 8388:1998 UNI EN ISO 4921:2005	-	
Mass per unit area	ISO 3801:1977 UNI EN 12127:1999	g/m²	
Width	UNI EN 1773:1998	cm	
Dyeing			
Colour Index	-	-	
PERFORMANCE CHARACTERISTICS			
Martindale Pilling test	UNI EN ISO 12945-2:2002	grade	
pH of water extract	UNI EN ISO 3071:2006	-	
Stretch properties	UNI EN 14704-1:2005	%	



Characteristics	Reference standard	Units
Dimensional change to washing	UNI EN ISO 6330:2012	%
	UNI EN ISO 3759:2011	
	UNI EN ISO 5077:2008	
Colour fastness		
Light Xenotest	UNI EN ISO 105 B02:2014	grade
Washing		
with mild detergent at 40°C	UNI EN ISO 105 C10:2008	grade
with commercial household detergent at 50°C	UNI EN ISO 105 C06:2010	grade
hand washing at 30°C	UNI 10994:2002	grade
Water	UNI EN ISO 105 E01:2013	grade
Sea water	UNI EN ISO 105 E02:2013	grade
Chlorine	UNI EN ISO 105 E03:2010	grade
Acid and alkaline perspiration	UNI EN ISO 105 E04:2013	grade
Dry and wet rubbing	UNI EN ISO 105 X12:2016	grade

Table 1 Technology description.

This section may also include:

- Name and contact information of organisation carrying out the underlying LCA study,
- Additional information about the underlying LCA-based information, such as assumptions, cut-off rules, data quality and allocation.
- Specific aspects regarding the production and the use of the product
- Existing environmental policy
- Environmental labels
- Manufacturer's trademark

5.4.4 CONTENT DECLARATION

The following materials and/or chemical substances shall be included in the EPD^{\otimes} , if contained in the product:

- All materials ≥ 0.5 % weight.
- The gross weight of material shall be declared in the EPD at a minimum of 99 % of one unit of product.
- All materials/substances that are regulated by compulsory standards or that are requested by the market.
- Materials/substances submitted to legal requirements shall be listed, materials/substances hazardous to health and the environment, being allergenic, carcinogenic, mutagenic or toxic to reproduction if present in such a concentration in the product that it meets requirements for being subjects to labelling according to the legislation (e.g. the European Directives on substances and preparations).



The lists can be complied according to the concentration level or the amount of material/product contained in a functional unit. Analytical and sampling methods shall be clearly indicated.

Information on the hazardous properties of materials and chemical substances should follow the requirements given in the latest revision of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)⁸, issued by United Nations or national or regional applications of the GHS.

As an example, the following regulations should be used for EPDs intended to be used in the European Union:

- Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures

5.4.4.1. Information about recycled materials

When a product is made in whole or in part with recycled materials, the provenience of the materials (pre-consumer or post-consumer) shall be presented in the EPD as part of the content declaration.

To avoid any misunderstanding about which material may be considered "recycled material", the guidance given in ISO 14021 shall be taken into account. In brief, the standard states that:

- only pre-consumer or post-consumer materials (scraps) shall be considered in the accounting of the recycled materials, and
- materials coming from scrap reutilisation (such as rework, regrind, or scrap generated in a process and capable of being reclaimed within the same process that generated it) shall not be considered as recycled content.

5.4.4.2. Information about packaging

As packaging is strongly connected with the product, the producer shall provide information about packaging in the EPD, when applicable. Packaging may be classified as:

- Distribution Packaging: packaging designed to contain one or more articles or packages, or bulk materials, for the purposes of transport, handling and/or distribution (ISO 21067-1:2016, Par. 2.2.6)
- Consumer Packaging: packaging constituting, with its content, a sales unit for the final user or consumer at the point of retail (ISO 21067-1:2016, Par. 2.2.7).

Consumer packaging is generally the outcome of eco-design processes, or other activities, under direct control of the organisation. Many critical categories with strict legal requirements belong to consumer packaging category like food contact packaging and pharmaceutical packaging.

The type and function of packaging shall be reported in the EPD.

A statement of the source of the materials (pre-consumer or post-consumer) shall be presented in the EPD when the packaging is made in whole or in part by recycled materials.

5.4.5 ENVIRONMENTAL PERFORMANCE

5.4.5.1. Environmental impacts

The indicators related to potential environmental impact listed in Table 2 shall be declared per functional unit or declared unit, and per life cycle stage.

PARAMETER		UNIT	UPSTREAM	CORE	DOWNSTREAM	TOTAL
Global	Fossil	kg CO₂ eq.				
warming potential	Biogenic	kg CO ₂ eq.				

⁸ The GHS document is available on www.unece.org.



(GWP)	Land use and land transformation	kg CO₂ eq.		
	TOTAL	kg CO₂ eq.		
Acidification pot	ential (AP)	kg SO ₂ eq.		
Eutrophication p	ootential (EP)	kg PO₄³- eq.		
Formation potential of tropospheric ozone (POCP)		kg C₂H₄ eq.		
Ozone-depleting potential ⁹		kg CFC11- equivalents		
Abiotic depletion	Abiotic depletion potential – Elements			
Abiotic depletion potential – Fossil fuels		MJ, net calorific value		
Water scarcity potential		m³ eq.		

Table 2 Indicators describing potential environmental impacts¹⁰.

Notes:

 Abiotic depletion potential is calculated and displayed as two separate indicators. ADP-fossil fuels include all fossil resources, while ADP-elements include all non-renewable material resources.

5.4.5.2. Specifications for GWP calculations

This section is adopted from the General Programme Instructions, Section A.9.

Both emissions to the atmosphere and removals from the atmosphere shall be accounted for the assessment of the overall GHG emissions of the product being assessed.

This assessment shall include the gases arising from both fossil and biogenic sources for all products, with the exception of human food and animal feed products.

Emissions and removals of biogenic carbon shall be reported separately.

Where some or all removed carbon will not be emitted to the atmosphere within the 100-year assessment period, the portion of carbon not emitted to the atmosphere during that period shall be treated as stored carbon. Following issues shall be taken into account:

- carbon storage might arise where biogenic carbon forms part or all of a product (e.g. wood fibre in a table), or where atmospheric carbon is taken up by a product over its life cycle (e.g. cement),
- while forest management activities might result in additional carbon storage in managed forests through the retention of forest biomass, this potential source of storage is not included in the scope of the International EPD® System.

GHG emissions offset mechanism shall not be used at any point in the assessment of the GHG emissions of the product. The organisation could declare its participation to some offsetting program in the other information section of the EPD® or single issue EPD.

5.4.5.3. Use of resources

The indicators for resource use based on the life cycle inventory (LCI) listed in Table 3 shall be declared per functional unit or declared unit, and per life cycle stage.

-

⁹ 20 year perspective

¹⁰ Please check www.environdec.com for the latest list of default impact categories, units and characterisation factors as they may have been updated compared to this table.



PARAMETER		UNIT	UPSTREAM	CORE	DOWNSTREAM	TOTAL
	Use as energy carrier	MJ, net calorific value				
Primary energy resources – Renewable	Used as raw materials	MJ, net calorific value				
	TOTAL	MJ, net calorific value				
	Use as energy carrier	MJ, net calorific value				
Primary energy resources – Non-renewable	Used as raw materials	MJ, net calorific value				
	TOTAL	MJ, net calorific value				
Secondary material		kg				
Renewable secondary fuels		MJ, net calorific value				
Non-renewable secondary fuels		MJ, net calorific value				
Net use of fresh water		m³				

Table 3 Indicators describing use of primary and secondary resources.

Notes:

- In order to identify the primary energy used as an energy carrier (and not used as raw materials), the parameter may be calculated as the difference between the total input of primary energy and the input of energy resources used as raw materials.
- Energy content of biomass used for feed or food purposes shall not be considered.
- The net use of fresh water does not constitute a "water footprint" as potential environmental impacts due to the water use in different geographical locations is not captured. For this indicator:
 - Evaporation, transpiration, product integration, release into different drainage basins or the sea, displacement of water from one water resource type to another water resource type within a drainage basin (e.g. from groundwater to surface water) is included.
 - In-stream water use is not included.
 - For water used in closed loop processes (such as cooling system) and in power generation only the net water consumption (such as reintegration of water losses) should be considered.
 - Seawater shall not be included
 - Tap water or treated water (e.g. from a water treatment plant), or wastewater that is not directly released in the environment (e.g. sent to a wastewater treatment plant) are not elementary water flows, but intermediate flows from a process within the technosphere.
 - Additional transparency in terms of geographical location, type of water resource (e.g. groundwater, surface water), water quality and temporal aspects may be included as additional information.

5.4.5.4. Waste production and output flows

Waste generated along the whole life cycle production chains shall be treated following the technical specifications described in the General Programme Instructions. When the amount of waste or the output flows is from the life cycle inventory (LCI) are declared, the indicators in Table 4 and Table 5 shall be reported per functional unit or declared unit, and per life cycle stage.

PARAMETER	UNIT	UPSTREAM	CORE	DOWNSTREAM	TOTAL
-----------	------	----------	------	------------	-------



Hazardous waste disposed	kg		
Non-hazardous waste disposed	kg		
Radioactive waste disposed	kg		

Table 4 Indicators describing waste production.

PARAMETER	UNIT	UPSTREAM	CORE	DOWNSTREAM	TOTAL
Components for reuse	kg				
Material for recycling	kg				
Materials for energy recovery	kg				
Exported energy, electricity	MJ				
Exported energy, thermal	MJ				

Table 5 Indicators describing output flows.

Notes:

- The parameters are calculated on the gross amounts leaving the system boundary of the product system in the LCI. If e.g. there is no gross amount of "exported energy, electricity" leaving the system boundary, this indicator is set to zero,
- The parameter "Materials for energy recovery" does not include materials for waste incineration. Waste incineration is a method of waste processing, when R1<60% (European Guideline on R1 energy interpretation), and is allocated within the system boundary.</p>
- In case there are never any flows of these types leaving the system boundary for a product category, the indicators may be removed by the PCR.

5.4.6 INFORMATION RELATED TO SECTOR EPDS

For sector EPDs, the following information shall also be included:

- a list of the contributing manufacturers that the Sector EPD covers,
- a description of how the selection of the sites/products has been done and how the average has been determined, and
- a statement that the document covers average values for an entire or partial product category (specifying the percentage of representativeness) and, hence, the declared product is an average that is not available for purchase on the market.

5.4.7 DIFFERENCES VERSUS PREVIOUS VERSIONS

For EPDs that have been updated, the following information shall also be included:

- a description of the differences versus previously published versions, e.g. a description of the percentage change in results and the main reason for the change;
- a revision date on the cover page

5.4.8 REFERENCES

This section shall include a list of references, including the General Programme Instructions (including version number), standards and PCR (registration number, name and version). The source and version of the characterisation models and the factors used shall be reported in the EPD.

- The underlying LCA
- The name, CPC code and version number of the PCR used



- Other documents that verify and complement the EPD[®]
- Instruction for recycling, if relevant
- The General Programme instructions of the International EPD® System

5.4.9 EXECUTIVE SUMMARY IN ENGLISH

For EPDs published in another language than English, an executive summary in English shall be included.

The executive summary should contain relevant summarised information related to the programme, product, environmental performance, additional information, information related to sector EPDs, references and differences versus previous versions.



6 GLOSSARY

CO₂ Carbon dioxide

CPC Central product classification

EPD Environmental product declaration

ISO International Organization for Standardization

kg kilogram

LCA Life cycle assessment
PCR Product Category Rules

SI The International System of Units

SO₂ Sulphur dioxide
UN United Nations



7 REFERENCES

CEN (2013), EN 15804:2012+A1:2013, Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products.

EPD International (2017) General Programme Instructions for the International EPD® System. Version 3.0, dated 2017-12-11. www.environdec.com

ISO (2000), ISO 14020:2000, Environmental labels and declarations - General principles

ISO (2004), ISO 8601:2004 Data elements and interchange formats - Information interchange - Representation of dates and times

ISO (2006a), ISO 14025:2006, Environmental labels and declarations – Type III environmental declarations – Principles and procedures

ISO (2006b), ISO 14040:2006, Environmental management - Life cycle assessment - Principles and framework

ISO (2006c), ISO 14044: 2006, Environmental management - Life cycle assessment - Requirements and guidelines

ISO (2013), ISO/TS 14067:2013, Greenhouse gases – Carbon footprint of products – Requirements and guidelines for quantification and communication

ISO (2014), ISO 14046:2014, Environmental management - Water footprint - Principles, requirements and guidelines

ISO (2017), ISO 21930:2017, Sustainability in buildings and civil engineering works -- Core rules for environmental product declarations of construction products and services



8 VERSION HISTORY OF PCR

VERSION 1.0, 2012-12-07

Original version. This PCR is an update of PCR 2008:05 Synthetic fibres woven.

VERSION 2.0, 2016-09-23

- Updated for compliance with version 2.5 of the General Programme Instructions
- Added in Product group classification the UN CPC 281 Knitted or crocheted fabrics
- Updated technical standards in Table 1
- Update § 6 System boundaries and Figure 1
- Editorial changes
- Extended validity

VERSION 2.1, 2019-04-30

- Updated in accordance with GPI 3.0 and new basic PCR.
- Updated PCR Basic Module

VERSION 2.11, 2019-09-06

- Clarified terms of use
- Editorial changes

VERSION 2.12, 2019-09-25

Editorial changes

VERSION 2.12, 2020-11-18

Extension of the validity of the PCR with 1 year until 2021-09-23. This extension of validity is allowed by Section 5.5.2.1 of the GPI, as the development of a new PCR replacing this PCR has been initiated and is expected to be available towards the end of 2021.

© 2020 EPD INTERNATIONAL AB YOUR USE OF THIS MATERIAL IS SUBJECT TO THE GENERAL TERMS OF USE PUBLISHED ON BY EPD INTERNATIONAL AB:S HOMEPAGE AT <u>HTTPS://WWW.ENVIRONDEC.COM/CONTACT/GENERAL-</u> TERMS-OF-USE/. IF YOU HAVE NOT REGISTERED AND ACCEPTED EPD INTERNATIONAL AB:S THE GENERAL TERMS OF USE, YOU ARE NOT AUTHORIZED TO EXPLOIT THIS WORK IN ANY MANNER. COVER IMAGE N/A